



WESTMINSTER

INTERNATIONAL LTD

Telephone : +44 (0)1295 756300

Fax : +44 (0)1295 756302

E-Mail : info@wi-ltd.com

Website : www.wi-ltd.com

WG 03T Broadband Indicator



WG 03T Broadband indicator of radio signals is designed to detect and determine the location of different signal sources (GSM, BT, WF, DECT, 3-4G, etc.), distinguish between continuous and pulsed signals, and to roughly estimate their radiation power.

The product significantly expands the range of input signals up to 74 dB, features second indication threshold to operate under high microwave background and has a built-in acoustic microphone jammer.

The product is powered by a Li-ion battery LIR2032 with a capacity of 40mAh.

MAIN ADVANTAGES

- Small size and weight
- Long operation of the device from the battery
- Simple control
- LED indication
- Monitoring of the discharge level
- Three operation modes
- Acoustic Jammer blocks the microphone of the detected device

SPECIFICATION

- Operating frequency: 400MHz-6GHz
- Detection range over the entire range: 0.5-1m/mW
- Dynamic range: 74 dB
- Indicator bitrate: 12
- Indication thresholds over the entire range: 0dB and + 12dB
- Power of acoustic jammer: more than 80 dB
- Battery life:
 - without signal -3000h,
 - with light indication -40h,
 - with sound indication -25h,
 - with vibroindication -1.5h,
 - LED flashlight 4h.
- Charging time: 1,5 h
- Dimensions: 48x32x12mm
- Weight: 20 g
- Case: Plastic