



WESTMINSTER

INTERNATIONAL LTD

Telephone : +44 (0)1295 756300

Fax : +44 (0)1295 756302

E-Mail : info@wi-ltd.com

Website : www.wi-ltd.com

WG Audio Probe



The WG Audio Probe is high performance microphone probe for covert listening operations through small gaps, keyholes and drilled holes.

The insertion probe is 6mm diameter x 330mm working length. A removable 1 metre lead connects the probe with an amplifier unit which is mountable on the belt of the operator.

A simple knob switch is on the front panel of the amplifier. Turn clockwise to switch on the unit, and further clockwise to increase the volume. A green LED indicator shows that the power is on.

STANDARD FEATURES

- Extremely sensitive
- Superb audio quality
- Lasts for up to 7 hours from a single 1 hour charge

SPECIFICATION

- Charger: Fast intelligent 12V charger with world mains plug adapters. Indicates red when charging and green when charged. Full operation manual supplied
- Headphones: High quality stereo headphones with 3.5mm jack plug. (Model subject to change)

SPECIFICATION

- Probe: 6 x 330mm stainless steel insertion tube. 4-pin plug to plug lead. Black anodised aluminium handle with 4-pin socket
- Microphone: Omnidirectional mini microphone. Output Impedance 4.4KOhm. Operating frequency 10,000Hz. Sensitivity -33dB+/- 3dB. Signal to noise ratio 30dB. 1.6VDC, 50µA
- Amplifier: 12VDC amplifier unit containing microphone pre amplifier and main amplifier in one unit. Battery pack: 12V NMH, 700mAHr capacity. Total current consumption <100mA. Front Panel: LED on indicator, volume control, 3.5mm headphone jack socket and 4-pin microphone socket. 3-pin charging socket. Fused T1.0A