



WESTMINSTER

INTERNATIONAL LTD

Telephone : +44 (0)1295 756300

Fax : +44 (0)1295 756302

E-Mail : info@wi-ltd.comWebsite : www.wi-ltd.com

WG Automatic Tyre Killers



The WG Automatic Tyre Killer range provides an efficient vehicle access control solution.

The various options available include: -

- Surface or shallow or submerge mounting.
- One or two directional driveway control.
- Different spikes length.

Making this a versatile security solution for different projects.

The unit uses built-in hydraulics making it an ideal solution for projects with severe climate conditions and those projects where there is a long distance of up to 100 metres between the control unit and tyre killer.

Applications

- Airport premises
- Business (office) centre
- Commercial areas
- Education institutions
- Financial institutions
- Governmental Institutions
- Hotels
- Military bases
- Nuclear power plants
- Production sites (industrial plants)
- Recreation areas
- Sport complexes
- Urban areas

TECHNICAL SPECIFICATIONS

Model	WG 370-02	WG 370-03	WG 370-04
Installation Type	Shallow mounted / Above the ground (with ramps)		
Drive	Hydraulic		
Spikes Direction	Bi-directional		
Width (W), mm	2000	3000	4000
Height, mm	170		
Load per axle, t	15		
Rising time, sec	3,0		
Lowering time, sec	2,0		
Operating temperature *, °C	-40/+60		
Power supply	1 phase 230 V, 50/60 Hz		
Protection level	IP 67 for road blocker - IP 55 for control box		
Materials	Structural steel C22 (galvanized and powder coated)		

*For temperatures lower than -10°C use the heating device
 For temperatures higher than +40°C use the cooler device

Model	WG 373-02	WG 373-03	WG 373-04
Installation Type	Shallow mounted/ Above the ground (with ramps)		
Drive	Hydraulic		
Spikes Direction	One-directional		
Width (w), mm	2000	3000	4000
Height, mm	170		
Load Per Axle, T	15		
Rising Time, Sec	3,0		
Lowering Time, Sec	2,0		
Operating Temperature *, °C	-40/+60		
Power Supply	1 phase 230 V, 50/60 Hz		
Protection Level	IP 67 for road blocker - IP 55 for control box		
Materials	Structural steel C22 (galvanized and powder coated)		

*For temperatures lower than -10°C use the heating device
 For temperatures higher than +40°C use the cooler device