



# WESTMINSTER INTERNATIONAL LTD

Telephone : +44 (0)1295 756300  
 Fax : +44 (0)1295 756302  
 E-Mail : info@wi-ltd.com  
 Website : www.wi-ltd.com

## WG 2500 & 4000 Portable Work Light



The WG 2500 & 4000 Portable Work Lights are highly durable work lights.

- It has been designed to withstand use in industrial environments.
- Featuring 2 output sockets to connect power tools and to link lights together.
- A rubberised protective rim and aluminium body will withstand knocks on building sites.

### KEY FEATURES

- 2,500 or 4000 Lumens
- 20 or 30 metre beams
- BS or EU sockets outlets - Connect tools or link lights together
- Impact resistant case and lens
- Carry handle - for easy transportation
- Die cast aluminium with rubberised protective rim
- Built-in kick back bracket
- 120° Beam angle
- Supplied with heavy duty, 1.8 metre HO7RN-F cable
- Optional tripod available



### SPECIFICATION

#### 2 Models Available

LIGHT OUTPUT	<b>2500 LUMENS</b>	<b>4000 LUMENS</b>
Beam	<b>20 METRES</b>	<b>30 METRES</b>
220V ~240V AV	DIMENSIONS 320mm x258mm x83mm	DIMENSIONS 250mm x450mm x540mm
IP67 RATING	<b>0.83 KG</b>	<b>1.09 KG</b>
		LINKABLE LIGHTS












It has a robust rubberised casing, built and designed to withstand the harshest industrial environments. Featuring 2 output sockets to connect power tools and to link lights together. With a carry handle and 4 level foldable bracket with fold flat design, ensures it is easy to transport.

## KEY FEATURES

- 2,500 Lumens
- 20 metre beam
- 2 x BS/EU sockets outlets - Connect tools or link lights together
- Robust rubberised casing for maximum protection
- Carry handle - for easy transportation
- Die cast aluminium with rubberised protective rim
- Diffused lens
- Built-in heat sink
- 4 Level foldable bracket - fold flat design
- Supplied with heavy duty 1.8 metre HO5RN-F cable + plug clip



## SPECIFICATION

 LIGHT OUTPUT	 2500 LUMENS		
 Beam	 20 METRES		 LINKABLE LIGHTS
 220V -240V AV	 IP54 RATING	 DIMENSIONS 290mm x230mm x95mm	 2.25 KG