

PR 4 Speed Gun



WESTMINSTER
GROUP PLC

Product Code: 1510-14

Key Benefits



Speed Reading updated 3 or 4 times per second



Range 3 to 750 metres



Speed Range 0 to 200 mph



Target Acquisition Time 0.3 seconds



Home Office Approved



Overview

The PR 4 measures the range and speed of approaching or departing vehicles using 200 laser pulses every second. The speed reading is updated 3 or 4 times a second in Continuous mode, or in Single mode the speed is captured immediately.

The narrow laser beam is just 75cm wide at 750 metres and provides pinpoint accuracy for targeting a single vehicle in a group, and so provides superior defence against laser jammers.

Both speed and range are displayed in the head-up display. Its 1:1 ratio allows both eyes to be open whilst operating, thus eliminating eye strain.

A choice of user-selectable, illuminated reticles is available to the operator.

All buttons are dual purpose giving quick access to all commonly used features without needing to enter the menu system.

A robust aluminium casing and rubber bumpers protect the lenses and rear panel display. The PR 4 is waterproof and dustproof and IP67 rated. The ergonomic pistol grip style handle provides excellent operator comfort. Traffic stats for 1000 events are stored and can be downloaded to a PC.

Features

Lightweight 1.25 kg

IP67 Rating

Temperature Range -15°C to +60°C

Standard AA Batteries

Range 3 to 750 metres

Speed Range 0 to 200 mph

Traffic Stats for 1,000 events

Applications

- Police
- Law Enforcement Agencies

Standard Features

- Accuracy +/- 3 mph
 - Choice of aiming reticles
 - Count up timer
 - HUD displays speed and range
 - Max beam width 75cm at 750m
 - Range 3 to 750 metres
 - Single or Continuous mode
 - Speed range 0 to 200mph
 - Speed reading "lock" mode
 - Target acquisition time 0.3 sec
 - Ergonomic pistol grip
 - High contrast, low power OLEO display
 - Home office approved
 - IP67 rated
 - Lightweight 2.75lbs (1.25kg)
 - Poor weather mode
 - Size: 155mmL x 225mmH x 110mm W
 - Supplied in ruggedised case
 - Temperature range -15C to +60C
 - Uses standard AA batteries
- Target acquisition time 0.3 sec
 - Ergonomic pistol grip
 - High contrast, low power OLEO display
 - Home office approved
 - IP67 rated
 - Lightweight 2.75lbs (1.25kg)
 - Poor weather mode
 - Size: 155mmL x 225mmH x 110mm W
 - Supplied in ruggedised case
 - Temperature range -15C to +60C
 - Uses standard AA batteries

Accessories

- Motorcycle tank bag
- Shoulder stock/tripod

