





UltralightEasy to handle and carry



Multifunction
Hospital
performance
on field



Maintenance Free
Durable and reliable
device which delivers
relentless ventilation,
and requires only
periodical filter
replacement



Energy Flex
Compatible with
rechargeable and
non-rechargeable
battery



Night VisionGoggles compatible

For use in:

Rotary & fixed wing aircrafts | Ambulances | Navy vessels including submarines Field hospitals | Ground units







Ventway Sparrow - Robust P/N: VWSP-900

Dimensions 165×167×60 mm | Weight 1.3 kg

Perfomance Data

Ventilation Modes	SIMV-VC-PS, CPAP, CPR (Invasive/Non-Invasive)
Quick Start Mode	Automatic Parameter Adjustment
Adult & Pediatric	Patient Weight >5 Kg (11Lb)
Tidal Volume	50-1800 ml
Breath Rate	1-60 BPM
Peak Inspiratory Pressure	0-65 cmH ₂ 0
Peak Inspiratory Flow	1-150 L/min
Trigger	2-10 cmH ₂ O, -3 to 10 L/min
PEEP	5-10 cmH ₂ O
Low Pressure 02 Source	21%- 95% ±5% O2
Humidity Level	5% to 95%
Atitude	up to 25,000 ft

Power Specifications

Rechargeable Battery Pack	Li 2850 mAh
Non-Rechargeable Battery Pack	Li 3000 mAH
External AC-DC Adaptor	90~264VAC 50/60Hz
External DC-DC Vehicle Adaptor	18~28VDC 4A max

Major Standards

IEC 60601-1, IEC 60601-1-2, IEC 60601-1-12, ISO 80601-2-12, ISO 10651-3, EN 794-3, RTCA DO 160G, EN 1789, MiL STD 810G, MiL STD 461G, MiL STD 1275

