

LONG TERM ACUTE CARE BED

WITH BED EXIT DETECTION SYSTEM



10" low height with built-in bed exit detection system to minimize falls

Seamless design to maximize infection control

Four casters with central brake to maximize staff efficiency and patient safety

LOW HEIGHT • EASY TO CLEAN • FULLY FEATURED



Clearance for lift and overbed table compatibility, even at lowest height



Four casters with central brake to minimize falls



Built-in bed exit system for improved detection reliability, available with smart screen



Multiple headboard and footboard designs to suit your decor



LONG TERM ACUTE CARE BED

WITH BED EXIT DETECTION SYSTEM

BED FEATURES

- Built-in bed exit alarm system
 2 levels of sensitivity
- 4 DC actuators
- Battery back-up
- 4 casters with central brake
- Open architecture
- 4 corner bumpers
- Integrated pump holder
- Nurse controls integrated into footboard
- One step Trendelenburg
- One step vascular foot position
- Patient control lockout
- Boostless™ Backrest System
- Compliant with standard IEC 60601-2-52

OPTIONAL FEATURES

- 10" / 25.4 cm low height
- Built-in bed exit alarm system
 - 3 levels of sensitivity (with smart screen)
- Remote bed exit alarm connectivity
- Bed exit side view lights
- Auto-contour
- Backrest angle indicator
- Programmable lowest height
- Patient surface length (80" or 84")
- 5" / 12.7 cm single or dual casters
- 120-volt / 5 A or 220-volt / 2 A insulated outlets with USB mobile device power outlets
- CPR release handle
- Roller type wall protection bumpers
- Downward motion interrupt
- Communication port (for upgradable bed software)
- Nightlights
- Smart screen on footboard control

Bed position indicator Bed exit event log Inform Message Center Maintenance menu

- Password management
- 2 or 5 function removable patient control
- Plastic headboard and footboard
 - Transport handles
 - Optional smart screen
- Wooden or laminated headboard & footboard
 - Choice of customized colors
- Patient mobilization helper (head end only)
- Foot end back-up control on the frame
- Patient control connector (Permanent or removable)

Accessories*

- Patient helper system
- Upright oxygen bottle holder
- IV poles (permanent & removable)
- * To see all accessories available, visit our website

Specifications for model FL36 / ook-cocoon

Overall length	88" / 224 cm or 92" / 234 cm
Overall width Siderails down Siderails up	39.25" / 100 cm 40.5" / 102.9 cm
Weight capacity	600 lb / 272 kg
Height range (to litter top) Low (with 5" / 12.7 cm dual casters) High (with 5" / 12.7 cm dual casters) Low (with 5" / 12.7 cm single casters) High (with 5" / 12.7 cm single casters)	10" / 25.4 cm 30" / 76.2 cm 11.5" / 29.2 cm 31.5" / 80 cm
Patient surface positioning Backrest Knee Gatch Trend. /Reverse Trend. Boostless™	0° to 60° 0° to 30° ± 16° 4" / 10.2 cm
Patient surface dimensions	35" x 80" or 84" 88.9 x 203.2 or 213.4 cm
Caster diameter	5" / 12.7 cm
Bed weight	336 to 369 lb / 152 to 167 kg

Electronics

Compliant with standard	IEC 60601-1 3 rd edition
Volts	120 V AC / 220-240 V AC
Ampere rating	4.25 A (9.25 A with 120 V outlets) / 2.15 A (4.15 A with 220 V outlets)
Current leakage	< 300 micro amps
Frequency	60 Hz / 50 Hz
Hospital grade plug	Yes
Battery type	Sealed rechargeable lead acid 1.2 Ah, 2 * 12 V

Umano Medical reserves the right to change specifications without notice.

Contact your local reprensentative to know which configuration is available in your region.



Umano Medical Inc.

L'Islet QC GOR 2C0 CANADA Toll

free number: 1 844 409-4030

information@umanomedical.com

230, boul. Nilus-Leclerc,

umanomedical.com





Exclusive Representative Alberta & Saskatchewan

Toll free number: 1 844-932-7773 umanomedical@mhcaremedical.com mhcaremedical.com