

## AN ALL-IN-ONE HOSPITAL BED FOR MULTIPLE CARE ENVIRONMENTS

med-surg | bariatric care | palliative care





One-step powered Infinite™ width expansion system, increased weight capacity, and low height all come together to improve staff efficiency, patient comfort, and safety.

Featuring Pilot Drive<sup>™</sup> – the first powered drive system to offer an unmatched combination of low height, underbed clearance, and manoeuvrability.

### **VERSATILITY · LOW HEIGHT · MOBILITY**



MEDICAL-SURGICAL Low height, ease of use, and ease of cleaning makes this bed ideal for med-surg environments.



BARIATRIC CARE
1060 lb weight capacity,
width expansion, and
an appealing design
encourages patient
autonomy and dignity for
baratric care.



PALLIATIVE CARE
Also known as the Cuddle
Bed, it is the only bed on the
market certified to be used
by two people.



PILOT DRIVE
Added mobility combined with enhanced versatility makes the ook snow ALL with Pilot Drive and integrated O2 bottle holders a unique solution for your bariatric patients in intensive care.



# AN ALL-IN-ONE HOSPITAL BED FOR MULTIPLE CARE ENVIRONMENTS

med-surg | bariatric care | palliative care

#### STANDARD FEATURES

- 11" low height with 5" dual casters
- Infinite<sup>™</sup> powered width adjustment
- Integrated scale system
- Smart screen, nurse controls and patient control lockout on footboard
- Integrated bed exit detection system 3 levels of sensitivity Bed exit side view lights
- Smart Nightlights<sup>™</sup>
- Remote bed exit alarm connectivity
- Boostless<sup>™</sup> Backrest System
- One hand release siderails
- · Liftable and flat deck covers
- Battery back-up
- Compatibility with mattresses within 48" width
- Programmable lowest height
- Nurse and patient controls integrated into siderails
- Integrated bed extender (35" x 4")
- CPR release handle
- Trendelenburg angle displayed on footboard
- Backrest angle indicator
- Patient restraint loops
- Integrated pump holder
- 120-volt / 5A insulated outlets (at foot end)
- Communication port (for bed software updates)
- Programmable Auto-Contour mode
- One-touch button groups

30-degree head of bed

One-button chair position

Flat bed position

Trendelenburg / Reverse Trendelenburg

Vascular foot position

#### **OPTIONAL FEATURES**

- 12.7" low height 6" dual casters
- Pilot Drive™ with or without O2 bottle holders (compatible with size E bottles)
- Downward motion interrupt
- Bed status monitoring
- Optional patient surface length (80" or 84")
- 120-volt/5A insulated outlets with USB mobile device power outlets
- Higher siderails (for 8" mattress)
- Foot end back-up control on the frame
- Roller type wall protection bumpers
- Additional nurse call port
- One-touch button groups

Backlit patient controls

Nurse call

Different styling options available

#### **ACCESSORIES**

Patient helper system (300 lb capacity) Upright oxygen bottle holder IV poles (permanent & removable) 4" bed extender cushion Removable patient controls Transport cart



ooksnow» ALL **SPECIFICATIONS** Product model 200-0000 Length Overall length (80" deck length) 90" / 228.6 cm Overall length (84" deck length) 94" / 239 cm Extended length Adds 4" / 10.1 cm with Pilot Drive Adds 1" / 2.5 cm with Pilot Drive / oxygen bottle holders Adds 2.25" / 5.7 cm Overall width Siderails down - 35" surface 39.8" / 101 cm Siderails up - 35" surface 41.5" / 105.4 cm Siderails down - 47" surface 51.5" / 130.8 cm Siderails up - 47" surface 52.8" / 134 cm Safe Working Load 1060 lb / 481 kg Height range (to deck top) Low (with 5" / 12.7 cm dual casters) 11" / 27.9 cm High (with 5" / 12.7 cm dual casters) 30" / 76.2 cm Low (with 6" / 15.2 cm dual casters) 12.7" / 32.3 cm High (with 6" / 15.2 cm dual casters) 31.7" / 80.5 cm Patient deck positioning **Backrest**  $0^{\circ}$  to  $60^{\circ}$ 0° to 30° Knee gatch Trend. / Reverse Trend. ± 16°  $\mathsf{Boostless}^{\mathsf{TM}}$ 5" / 12,7 cm Patient deck dimensions Width 35" to 47" / 89 cm to 119.4 cm 80" or 84" / 203 cm or 213 cm Length Adds 4" / 10.1 cm Extended Length

Compliant with standards IEC 60601-1 and IEC 60601-2-52. Certified for use by two people (referring to one patient and one bystander.)

#### **ELECTRONICS**

Caster diameter

with Pilot Drive

Volts	120 V AC
Ampere rating	4.25A (9.25A with 120V outlets)
Current leakage	Compliant with IEC 60601-1
Frequency	60 Hz
Hospital grade plug	Yes
Battery type	Sealed rechargeable lead acid 1.2Ah, 2 * 12V
Battery type (Pilot Drive)	Sealed rechargeable lead acid 16.5Ah, 2 * 12V
Scale system accuracy	1% with a maximum difference of 2.2 lb / 1 kg (in all bed positions)
Scale system accuracy (EC)	OIML Class III ± 1 kg

Umano Medical reserves the right to change specifications without notice.

#### Umano Medical Inc.

230, boulevard Nilus-Leclerc L'Islet QC G0R 2C0 CANADA Toll free number : 1 844-409-4030 information@umanomedical.com umanomedical.com



### **Exclusive Representative Alberta & Saskatchewan**

5" or 6" / 12.7 cm or 15.2 cm

6" / 15.2 cm

Toll free number: 1 844-932-7773 umanomedical@mhcaremedical.com mhcaremedical.com