

# REKOLA

## REFLEX G MOPCLOTH 100% UMF

### Make a difference with REFLEX:



#### Outstanding Performance & Versatility:

Deep Cleaning, Multifunctional and Ergonomical Up to 50 sqm more per mopcloth



#### Climate & Eco friendly:

Less water and chemicals, Residue Free Cleaning




#### Improves cleaning economy:

Saves time and space and cut total costs



Product code	Color code	Dimension	
18-4050	blue	54 x 22,5 cm	<b>REFLEX G MOPCLOTH 100% UMF</b> , Multiple use, 88 grs/pcs
18-4054	red	54 x 22,5 cm	<b>REFLEX G MOPCLOTH 100% UMF</b> , Multiple use, 88 grs/pcs

**Package:** 5 pcs pp bag  32 pcs 5-pack per transport box

### Application areas:

The REFLEX 2-in-1 cleaning system is designed for all types of smooth and sealed hard top floorings. Main application areas, in case of less conditioned floors:



**Public Areas & General Buildings**



**Food Industry & HoReCa**

### How to use the system:

REFLEX G MOPCLOTH is double sided and is used in conjunction with REFLEX POWER SQUEEGEE 50 cm and REFLEX EXTENDABLE HANDLE 100/180 cm.

#### CHARGING:

REFLEX G MOPCLOTH can be pre-prepared/charged with clean tap water or processed water. Optional: Chemicals suitable for UMF can be diluted according to manufacturer's instructions.

#### CHARGING G MOPCLOTHS ON THE TROLLEY:

1. Put G MOPCLOTHS in a container, e.g. 6 Ltr. Rectangle bucket or box with lid.
2. Poor the desired fluid equally over the cloths inside the container.
3. Leave for a while with closed lid. Ready to clean!

#### ABOUT DOSING:

Avoid overdosing regardless the charging liquid.

Some chemicals may cause damage to user material and or environment.

Depending on floor circumstances, charge the G MOPCLOTH with 60-120 ml per MOPCLOTH.

### Eco Labeled:



3083  
0027




### Rekola support Residue Free Cleaning.


Rekola is part of a group of manufactures determined to eliminate residue of dirt and chemicals that can harm people's health REFLEX G MOPCLOTHS are designed to reduce and remove residue that resist traditional cleaning methods. For more information please contact Rekola

# REKOLA

## Maintenance

<b>Laundry:</b> 	<p>Rinse twice cold to ensure all cleaning chemicals are removed.            Main program for synthetic fibers at 60°C or less is preferred.            Rinse twice after ensuring all laundry agents are removed.            Adjust temperatures and water volumes accordingly.            Machine drums can be filled with MOPCLOTHS up to 80% load (According Weber &amp; Leucht laundry test DIN EN ISO 6330)            In case of drying use tumble drying at 60°C or less.            Do not use bleach or softener.            Low water level during processing or overloading washing machine (max 80% of door window) may cause irreversible damage to cloths.</p>
--	---

<b>Disinfection:</b>	<p>Non-bleach disinfectant* laundry agent and autoclaving may be used if required            *e.g. peroxide based; this may affect colors.</p>
----------------------	--

<b>Durability:</b> 	<p>500 washing cycles at 60°C or 200 washing cycles at 85°C. Rough surfaces like safety flooring may influence reduce lifetime expectations.</p>
---	--

## Components

<b>Body:</b>	<p>50% split Ultra Microfiber/ 50% PES; 90% PES 10 PA and F= 0,154 Dtex.</p>
--------------	--

<b>Borders:</b>	<p>Overlock 100% PES. Sliding strip TPU and PES Mesh</p>
-----------------	--

## Characteristics

<b>Shrinkage:</b>	<p>SGS tested &lt; 6% at recommended washing instructions. This can cause slight deformation, this does not affect the functionality.</p>
-------------------	---

<b>Color fastness</b>	<p>4-5. <i>standard request ≥ 3-4</i></p>
-----------------------	---

<b>Charging</b>	<p>3,9 DAC value. <i>standard request minimum 2,5</i></p>
-----------------	---

<b>Abrasion</b>	<p>10,5 Gloss differential. <i>standard request &lt; 20</i></p>
-----------------	---

<b>Weber &amp; Leucht S301/1.3 dirt removal</b>	<p>Ceramic Tile SF 11    Dust A23    Damp    97%    <i>standard request ≥ 70</i></p>
	<p>PVC- Flooring PL-03    Dust A23    Damp    90%    <i>standard request ≥ 70</i></p>
	<p>Ceramic Tile SF 11    Muddy dirt A05    Damp    100%    <i>standard request ≥ 70</i></p>
	<p>PVC- Flooring PL-03    Muddy dirt A05    Damp    100%    <i>standard request ≥ 70</i></p>

<b>Non-Touch</b>	<p>In conjunction with REFLEX POWER SQUEEGEE, dirty cloths are not touched when demounting.</p>
------------------	---

<b>Patent:</b>	<p>FI201000028 Floor Maintenance Device and Cloth.</p>
----------------	--

<b>Disposing:</b>	<p><b>REFLEX G MOPCLOTHS</b> are purely synthetic: may be used for recycling programs; or because of their high energy value and with no emissions other than CO<sub>2</sub> and water can be safely disposed by controlled energy-supply programs.</p>
-------------------	---

## Guarantee

500 times use and laundries according producers guidelines at 60°C, under general hygiene cleaning circumstances, at a maintained non-safety sealed floor.  
 Extended usage can be achieved if optimal laundry and cleaning conditions are considered.  
 For instruction and details ask your distributor.