



an EnerSys company

CXC HP HV-ADIO

CXC HP Smart Peripheral



- CXC HP series ADIO peripheral with flexible rack, panel, and DIN mounting options
- Enables High Voltage (125/220Vdc) system support using the advanced CXC HP Control platform
- I/O expansion via CAN bus for advanced site monitoring applications, including support for future growth
- Integrated Ground Fault Detection (GFD) to alarm system fault conditions
- On board DC-DC converter permits use with standard CXC HP low voltage controllers

The Cordex® CXC HP HV-ADIO brings advanced control and monitoring to Alpha Cordex 125/220Vdc rectifiers and systems.

The HV-ADIO is part of the CXC HP series of advanced I/O peripheral incorporating flexible mounting, high accuracy, and the advanced features in the HP control platform.

The HV-ADIO provides a variety of analog inputs, digital inputs and high voltage rated relay outputs. The ADIO device is seamlessly recognized by the CXC HP control platform which also provides advanced setup wizards to create high voltage DC systems using Cordex rectifiers.

An integrated Ground Fault Detection (GFD) circuit is also provided to enable visibility to earth leakage currents. This feature can be easily disabled for operators who wish to use 3rd party GFD devices.

Cordex CXC HP controllers and ADIO peripherals ensure effortless operation and management capability to satisfy the most demanding and advanced energy system applications.

CXC HP HV-ADIO Smart Peripheral

P/N: 0180057

07/2020

Electrical	
Input Voltage:	90 to 300Vdc
Input Power:	50W (125Vdc 0.4A; 220Vdc 0.2A)
Output Power:	30Vdc; Max 1A, 30W (For feeding low voltage CXC HP controller)
DCCT Power:	±15Vdc
Features	
Local Alarms:	Power ON (Blue) Communications OK (Green)
Communication Ports:	CAN In/Out (RJ12 Offset)
Ground Fault Detection:	1 user configurable (Adjustable up to 15mA) on V2 input channel
Controller I/O:	
Voltage Inputs:	2 (±300Vdc)
Current Shunt Inputs:	1 (25 to 200mV)
DCCT Current Inputs:	2 (±10Vdc signal)
Temperature Inputs:	2
Digital Inputs:	4 (Contact closure detect – 5Vdc Max)
Relay Outputs:	6 (Form C, 220Vdc 50W max)
Mechanical	
Mounting:	CXC HP 3U rack panel mount (0180046) or DIN/Panel mounting
Dimensions:	mm: 198H x 84W x 38D inches: 7.8H x 3.3W x 1.5D
Weight:	1kg (2lbs)

Environmental	
Temperature:	
Extended:	-40 to 65°C (-40 to 149°F)
Humidity:	0 to 95% RH non-condensing
Elevation:	-500 to +4000m (-1640 to 13124ft)
Agency Compliance	
Safety:	CAN/CSA-C22.2 No 60950-1-07+Am1+Am2 ANSI/UL 60950-1-2014 IEC 60950-1:2005 (Second Edition) + Am 1:2009 + Am 2:2013 CE marked
EMC:	EN 61000-6-3 EN 55032 EN 61000-6-2
Emissions:	FCC CFR 47, Part 15 Subpart B Class B ICES-003 Class B EN 55022 Class B
Immunity:	EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6



Worldwide Corporate Offices			
Headquarter Germany Hansastrasse 8 D-91126 Schwabach Tel: +49 9122 79889 0 Fax: +49 9122 79889 21 Mail: info@alpha-outback-energy.com	Eastern Europe ee@alpha-outback-energy.com	France and Benelux fbnl@alpha-outback-energy.com	Russia russia@alpha-outback-energy.com
	Middle East me@alpha-outback-energy.com	Spain spain@alpha-outback-energy.com	Africa africa@alpha-outback-energy.com

Alpha and Outback Energy GmbH reserves the right to make changes to the products and information contained in this document without notice. Copyright © 2020 Alpha and Outback Energy GmbH. All Rights reserved.