

SPECTRUM F1600 Ferrule Placement

<u>Pt #</u>	<u>Size</u>	<u>Location</u>	<u># Per Car</u>
15/1001	5/16" x 1/4" Thin	Upper A-Arms inner sphericals - Ft & Rr	8
15/1002	5/16" x 1/4" Thick	Front Toe Link	8
15/1003	3/8" x 1/4" Thin	Rear Toe Link w/ RAM6T rod end	4
15/1004	3/8" x 1/4" Thick	Ft & Rr Push Rod Turnbuckle w/ RAM6T rod end Ft Upper A-Arms inner w/ RAM6T rod end	4 8
15/1005	7/16" x 5/16"	Lower A-Arms Ft & Rr inner w/ RAM7T rod end Push Rod lower Ft & Rr w/ RAM7T rod end	12 8
15/1006	7/16" x 3/8"	Lower Ft A-Arm inner w/ RAM7T rod end	4
15/1007	1/2" x 5/16"	Upper A-Arm Ft outer spherical end	4
15/1008	1/2" x 3/8"	Lower A-Arm Rear outer spherical end	4
15/1009		Upper A-Arm Ft outer spherical end - Upgraded only replaces 15/1007	2
		<u>Total</u>	64

Ferrule Placement by Application

Ft Toe Link (1/1027)	4 - 15/1002 per link
Ft Lower A-Arms (1/1029B & 1030B)	2 - 15/1005; 2 - 15/1006; per arm
Ft Upper A-Arms (1/1028B)	2 - 15/1007; 2 - 15/1004; 2 - 15/1001; per arm 2 - 15/1009 (Outer on upgraded arm)
Rr Lower A-Arms (1/1039B & 1040B)	2 - 15/1008; 4 - 15/1005; per arm
Rr Upper A-Arms (1/1054)	4 - 15/1003; 4 - 15/1001; per arm
Push Rods Ft & Rr (1/1031 & 10491)	2 - 15/1004; 2 - 15/1005; per rod