

Providing the allure of a wave motion coupled with two-tone design where the dominant color changes based on your perspective, this co-operative use of design and colors offers an alternative modern look that creates tranquility and connected experiences in spaces that demand sound control.

## Don't Mess with A Good Thing, Perfect It.

Meticulously crafted like your future depends on it, because it does.



# **Specifications**

Product Name	Tidal Baffle
Content	6–7lb fiberglass board with optional tackable & high-impact resistant facers, 100% post-consumer recycled polyester fabric
Thickness	2"
Unit Length	96"
Unit Height	15"
Weight	1.6 lbs/sq ft
Edge Options	Square or Beveled
Sound Performance	ASTM C423-17: NRC 2" = 1.31
Fire Performance	ASTM 84 Class A
Environmental	Low VOC emissions, woven fabrics are FR (Flame Retardant) free and compliant with CAL AB 2998.
Maintenance	Vacuum to remove any loose dirt or dust. You may use a soft or plastic bristle brush to loosen it. Avoid excess pressure. Compressed air can also be used to dust the material in difficult or large installations. Remove ordinary dirt and smudges with a mild soap and water solution and a clean, soft cloth or towel. Dry with a soft lint-free cloth or towel. A melamine magic eraser can be used for more difficult stains. Always apply any cleaning methods to a small area first to test effectiveness and result.
Warranty	5 years
Unit of Sale	Per unit

## **Price**



#### Snap the QR Code or visit sonusna.com to see pricing.


Sonus is the only manufacturer to have published universal pricing because:

- 1) We got nothing to hide.
- 2) We are here for you: faster, easier, straightforward.

Sonus creates the perfect experience for each person in any moment.


## Construction & Hardware

Side exit cable gripper



# Designs

#### Panel A






Front

Back

#### Panel B





Front

Back


## **Colors**

We currently offer over 40 standard colors thanks to our partnership with Burch. See our Sonus Standard Fabrics document on the next page for a complete listing.

We also carry a wide array of other acoustic fabrics and colors by Guilford of Maine, Knoll, Maharam, and more.

### **Test Results**

#### 2" Fabric Baffle



Freq (Hz)	Absorption Coefficiency
160	0.19
250	0.63
500	1.19
800	1.63
1250	1.74
2000	1.69
3150	1.58
NRC	1.31

The Noise Reduction Coefficiency (NRC) is calculated as the arithmetic average of the absorption coefficients in the shaded bands only (250, 500, 1250 & 2000 Hz).

ASTM C 423-17: Type J Mounting - using 8 baffle units suspended with aircraft wire. 12" oc to simulate a typical baffle installation.





#### **Standard Fabrics**

#### **Prime Time**

