

PVC7335



PVC GLOVE - LENGTH 35 CM

Ref. PVC7335



Product specifications

PVC on interlock cotton lining. Length: 35 cm. Thickness 0,90 mm.

Support: interlock cotton.

Coating: 100% cured and vulcanised PVC.

COLOUR

Red

SIZE

10

Product Use - Risks



BIOLOGICAL



Wearing



CHEMICAL



PARTICULES



Agriculture / Green areas



Heavy industry



Mining

CHEM D-FINDER



Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements
5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

3: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

3: Resistance to tear (from 1 to 4)

1: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE C: Type C - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 1 chemicals at level 1 according to EN16523-1: 2015 (from 1 to 6).

:: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.

K 6 > 480 mn: Caustic soda 40% (K) CAS 1310-73-2



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro-organisms risks.

BACTERIA + FUNGI :: BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.



References

References	Bar code	COLOUR	SIZE		
PVC733510	3295249020200	Red	10	120	12