



Anti-scratch



UV / IR



Shock

Safety Spectacle
Model: RAY SMOKE

IS 5983, ANSI Z87.1, EN 166, CE

INDUSTRY

Construction & projects
Cement
Automotive
Power & utilities
Metals & minings

IDEAL APPLICATIONS

Material handling
Dusty area
Assembly line
Packaging
Medical applications

SPECIAL FEATURES



LIGHT WEIGHT



99.9% UV PROTECTION



HARD COATING



LOW IMPACT RESISTANT

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	9.75 base curve, wrap around design w/side protection
Nose piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula
Hinge	Polycarbonate	5 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Smoke	1	5-2.5	F (45m/s)	K	20 g.

FEATURES

Polycarbonate temple with polycarbonate lens

Snug-fitting wrap around lens provides perfect impact protection around the eyes

Hard coating on lens

Lens filters out 99% of harmful UV light

Close-fitting unitary front with dual 9.75 base curvature offers wide and unobstructed vision

Soft temple tips

Incredibly light, resilient & durable protective eyewear for all day wear

Fashionable design resembles spectacle, suitable for both men and women

Suitable for different work environment

APPLICATION

Protects eyes exposed to low-level impacts

Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2years

Do not store in direct / high heat or sunlight as this may distort the colour

Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING

Clean it with the soft cloth

PACKING

100 pieces per carton