



INDUSTRY	IDEAL APPLICATIONS
Construction & projects	Material handling
Cement	Dusty area
Automotive	Assembly line
Power & utilities	Packaging
Metals & minings	Medical applications

SPECIAL FEATURES				
LIGHT WEIGHT	99.9% UV PROTECTION	HARD COATING	LOW IMPACT RESISTANT	

Safety Spectacle Model: ELK CLEAR	

IS 5983, ANSI Z87.1, EN 166, CE

COMPONENT	MATERIAL	ADVANTAGE
Lens	Polycarbonate	10 base Curve, Wrap around design w/side protection
Nose piece	Polycarbonate	Universal, integral to lens
Temple	Polycarbonate	Spatula with soft tip end
Tip	PVC	Slip on the temple
Hinge	Polycarbonate	3 barrel type
Screw	Stainless steel	Standard hinge screw

LENS OPTIONS	OPTICAL CLASS	FILTER	IMPACT RESISTANCE	COATING	WEIGHT
Clear	1	2-1.2	F (45m/s)	К	20 g.

FEATURES
Polycarbonate temple with polycarbonate lens
Snug-fitting wrap around lens provides perfect impact protection around the eye
Hard coating on lens
Lens filters out 99.9% of harmful UV light
On-piece lens, with dual 10 base curvature
Lens offers users the clearest and the most panoramic view without obstruction
Modern temple design& soft temple tips contours to fit head shapes without stress
Incredibly light, resilient & durable protective eyewear for all day wear
Fashionable design resembles spectacle, suitable for both men and women
Suitable for different work environment

AΡ	PL	IC/	١T١	10	V

Protects eyes exposed to low-level impacts

Best used for protection against flying small fragments

STORAGE

Can be stored in the dark for up to 2 years

Do not store in direct / high heat or sunlight as this may distort the colour $% \left(1\right) =\left(1\right) \left(1\right) \left($

Can be stored and transported in their original cartons at ambient temperature (0° C to +30° C)

CLEANING	PACKING
Clean it with the soft cloth	100 pieces per carton