

Article number: 1060534

## 5W-30 DPF-4 Plus 5W-30 C4 DPF

### Motor Oil for Petrol and Diesel Engines

#### DESCRIPTION

**DEUTSCHÖL 5W-30 DPF-4 Plus** is a Low SAPS low-friction motor oil based on advanced HC synthesis technology. Specially formulated for use in modern Renault diesel engines equipped with particulate filter and NOx-storage catalytic converter.

#### THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 5W-30  
ACEA C4

MB 226.51, 229.51  
Renault RN 0720

#### ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

#### TYPICAL CHARACTERISTICS

##### Properties

Density at 15°C

CCS -30 °C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

##### Testing according

DIN 51757

ASTM-D 5293

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

##### Data Unit

0,855 g/ml

5800 cP

< -35 °C

74 mm<sup>2</sup>/sec

11,8 mm<sup>2</sup>/sec

155

Article number: 1060534

## AVAILABLE PACKAGING



Item-number:.

1060534-1

1060534-4

1060534-5

1060534-20



Item-number:

1060534-60

1060534-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.

Please note: Our products may not be used in aircraft and spacecraft or parts thereof.