

Article number: 1060020

OW-20 Global Ultra OW-20 GF-5 Combisynt Motor Oil for Petrol Engines

DESCRIPTION

DEUTSCHÖL OW-20 Global Ultra is for gasoline engines according to the requirements of many American and Asian vehicle manufacturers. A high fuel saving is guaranteed..

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE OW-20
API SN/RC
ILSAC GF-5
Chrysler MS-6395
Fiat 9.55535-CRI/ GSX
Ford WSS-M2C-947 A

GM DXI-Gen2
GM 6094 M
Daihatsu, Honda, Hyundai, Isuzu, KIA, Mazda, Mitsubishi,
Nissan, Subaru, Suzuki, Toyota, Lexus

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties

Density at 15°C
CCS -35 °C
Pourpoint
Viscosity at 40 °C
Viscosity at 100 °C
Viscosity Index

Testing according

DIN 51757
ASTM-D 5293
DIN ISO 3016
DIN 51562
DIN 51562
DIN ISO 2909

Data	Unit
0,849	g/ml
5200	cP
< -40	°C
45	mm ² /sec
8,3	mm ² /sec
162	



Article number: 1060020

AVAILABLE PACKAGING



Item-number:..

1060020-1

1060020-4

1060020-5

1060020-20



Item-number:

1060020-60

1060020-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.

Please note: Our products may not be used in aircraft and spacecraft or parts thereof.