

Article number: 1331040

10W-40 United SL Super 10W-40 Economy

Motor Oil for Petrol and Diesel Engines

DESCRIPTION

DEUTSCHÖL 10W-40 United SL Super is a semi-synthetic low friction motor oil, perfectly suitable for all-year use in modern petrol and diesel engines. Also at a constant short-haul traffic passenger car-, transporter- and light truck engines are ideally protected. Specially suitable for turbocharger- and catalysts operations as well as multi-valve engines and diesel direct-injection systems.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-40	MB 229.1, MB 228.1
API SL/CF	VW 500.00 (obsolete)
ACEA A3/B4	VW 501.01, 505.00

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals
- improved fuel efficiency

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,865	g/ml
CCS -25 °C	ASTM-D 5293	5100	cP
Pourpoint	DIN ISO 3016	< -30	°C
Viscosity at 40 °C	DIN 51562	92	mm ² /sec
Viscosity at 100 °C	DIN 51562	14	mm ² /sec
Viscosity Index	DIN ISO 2909	155	
Base Number (TBN)	ASTM-D 2896	10,2	mgKOH/g

Article number: 1331040

AVAILABLE PACKAGING



1L

Item-number:..

1331040-1



4L

1331040-4



5L

1331040-5



20L

1331040-20



60L

Item-number:

1331040-60



205L

1331040-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.

Please note: Our products may not be used in aircraft and spacecraft or parts thereof.