

Article number: 1331540

10W-30 Mixed Fleet Basic

Modern Motor Oil for Petrol and Diesel Engines

DESCRIPTION

DEUTSCHÖL 10W-30 Mixed Fleet Basic is a premium multigrade motor oil, suitable for use in passenger car petrol and diesel engines as well as truck diesel engines, both turbocharged and non-turbocharged. Perfectly suitable as all-year oil for the mixed vehicle fleet. The universal properties also enable the application in construction machines, stationary engines, tractors and various small machines.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-30	Allison C4,
API SL/CF/CG-4	MAN 3275, MAN 271
ACEA A3/B4/E3	MTU Level 1, Level 2
MB 228.3, 228.1, 229.1	Renault RD/RGD
Volvo VDS	VW 501.01, 505.00

ADVANTAGES

- excellent wear protection
- outstanding oxidation- and temperature stability
- low friction losses
- optimum engine cleanliness due to excellent cleaning properties
- long oil changing intervals

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,860	g/ml
CCS -25 °C	ASTM-D 5293	6100	cP
Pourpoint	DIN ISO 3016	< -30	°C
Viscosity at 40 °C	DIN 51562	83	mm ² /sec
Viscosity at 100 °C	DIN 51562	11,8	mm ² /sec
Viscosity Index	DIN ISO 2909	135	
Base Number (TBN)	ASTM-D 2896	10,8	mgKOH/g



Article number: **1331540**

AVAILABLE PACKAGING



Item-number:.

1331540-1

1331540-4

1331540-5

1331540-20



Item-number:

1331540-60

1331540-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.

Please note: Our products may not be used in aircraft and spacecraft or parts thereof.