

Article number: 1091046

DEM 10W-40 Mega Truck LA

Motor Oil for Trucks and Commercial Vehicles

DESCRIPTION

DEUTSCHÖL 10W-40 Mega Truck LA. OEM (Original Equipment Manufacturer) truck-oil specially formulated for Euro IV and V diesel engines equipped with modern exhaust aftertreatment systems for example EGR (exhaust gas recirculation), SCR (AdBlue technology) and DPF (diesel particulate filter).

ORIGINAL APPROVAL

MB-Approval 228.51

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 10W-40

API CI-4

ACEA E6, E7, E9

Cummins CES 20076, 20077

MAN M3477, 3271-I

Scania LA

DAF

MTU Typ 3.1

Renault RLD-2, RXD, RGD

Volvo VDS-3, CNG

Cat ECF-Ia,

Mack EO-N, EO-M Plus

Deutz DQC IV-10LA

TYPICAL CHARACTERISTICS

Properties

Density at 15°C

CCS -25 °C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Testing according

DIN 51757

ASTM-D 5293

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

Data Unit

0,857 g/ml

5200 cP

< -30 °C

92 mm²/sec14,2 mm²/sec

160

Article number: 1091046

Available Packaging



Item-number: 1091046-1 1091046-4 1091046-5 1091046-20



Item-number: 1091046-60 1091046-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning.

Please note: Our products may not be used in aircraft and spacecraft or parts thereof.