

Article number: 1091540

## 15W-40 Super Truck

### Motor Oil for Trucks and Commercial Vehicles

#### DESCRIPTION

**DEUTSCHÖL 15W-40 Super Truck** is a premium motor oil, suitable for all-year use in all heavily loaded naturally aspirated and turbo diesel engines of the Euro I, II, III and IV class.

Special formulation ensures longer oil change intervals up to 80,000 km at a high wear protection (please observe manufacturer's instructions). Also suitable for use in various passenger car engines. Suited for fuels with a maximum sulphur content of 0.5 wt.-%.

#### THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 15W-40  
API CI-4/SL/CF, ACEA A3/B4, E7  
Caterpillar ECF-1a, ECF-2  
Cummins CES 20076/20077/20078  
DDC 93K215  
IVECO  
JASO DHD-1  
Mack EO-M, Mack EO-N  
MAN M 3275-1

MB 228.3, MB 229.1  
MTU Typ 2  
Renault RLD, RLD-2  
Volvo VDS-3  
VW 501.01, VW 505.0  
CES 20071, 20072  
DAF  
Scania LDF, Scania LDF-2  
Deutz DQC 3-10

#### TYPICAL CHARACTERISTICS

##### Properties

Density at 15°C  
CCS -20 °C  
Pourpoint  
Viscosity at 40 °C  
Viscosity at 100 °C  
Viscosity Index  
Base Number (TBN)

##### Testing according

DIN 51757  
ASTM-D 5293  
DIN ISO 3016  
DIN 51562  
DIN 51562  
DIN ISO 2909  
ASTM-D 2896

Data	Unit
0,865	g/ml
5800	cP
< -25	°C
102	mm <sup>2</sup> /sec
14	mm <sup>2</sup> /sec
139	
11,5	mgKOH/g

Article number: 1091540

## Available Packaging



Item-number: 1091540-1 1091540-60-4 1091540-5 1091540-20



Item-number: 1091540-60 1091540-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.