

Article number: 1092053

## 20W-50 Truck

### Motor Oil for Trucks and Commercial Vehicles

#### DESCRIPTION

**DEUTSCHÖL 20W-50 Truck** is a high-quality motor oil, suitable for all-year use in all heavily loaded naturally aspirated and turbo diesel engines of the Euro I, II, III and IV class. Selected additives guarantee high engine cleanliness with high wear protection. This ensures oil change intervals up to 45,000 km (please observe manufacturer's instructions). Suited for fuels with more than 0.5 wt.-% sulphur content.

When using high-sulphur fuels, the oil change intervals should be reduced..

#### THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 20W-50  
API CH-4/SL/CF  
ACEA A3/B4, E3  
MAN M 3275-1  
MAN 271  
MB 228.3, MB 228.1, MB 229.1  
MTU Level I+2

Renault RD/RGD  
Volvo VDS  
Mack EO-M+  
Cummins CES 20077  
Caterpillar ECF-Ia  
Allison C4  
VW 501.01, VW 505.001

#### TYPICAL CHARACTERISTICS

##### Properties

Density at 15°C  
CCS -15 °C  
Pourpoint  
Viscosity at 40 °C  
Viscosity at 100 °C  
Viscosity Index  
Base Number (TBN)

##### Testing according

DIN 51757  
ASTM-D 5293  
DIN ISO 3016  
DIN 51562  
DIN 51562  
DIN ISO 2909  
ASTM-D 2896

##### Data Unit


0,887 g/ml  
5200 cP  
< -20 °C  
165 mm<sup>2</sup>/sec  
19 mm<sup>2</sup>/sec  
130  
11 mgKOH/g

Article number: 1092053

## Available Packaging



Item-number: 1092053-1 1092053-4 1092053-5 1092053-20



Item-number: 1092053-60 1092053-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

