

Article number: 4698090

80W-90 GL-5 LS

Hypoid Gear Oil Limited Slip

DESCRIPTION

DEUTSCHÖL 80W-90 GL-5 LS for heavily loaded axle drives of all types, where API GL5 specification is prescribed. The LS quality (Limited Slip additives) prevents from the unwanted slide and slip effect. Specially recommended for use in axles and limited slip differentials.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 80W-90
API GL-5 Limited Slip
Ford M2C104-A,
MAN 342 M1
MAN 342 M2

MB 235.0
MB 235.6
MIL-L-2105 C/D
ZF TE-ML 01, 05A, 05C, 07A, 12E, 16B-C, 17B, 19B, 21A

TYPICAL CHARACTERISTICS

Properties

Density at 15°C
Pourpoint
Viscosity at 40 °C
Viscosity at 100 °C
Viscosity Index

Testing according

DIN 51757
DIN ISO 3016
DIN 51562
DIN 51562
DIN ISO 2909

Data Unit

0,884 g/ml
< -20 °C
145 mm²/sec
15 mm²/sec
108



Contains Long-chain alkyl amine. May produce an allergic reaction.



Article number: **4698090**

AVAILABLE PACKAGING



Item-number: 4698090-1 4698090-4 4698090-5 4698090-20



Item-number: 4698090-60 4698090-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.