

Article number: 4777580

## 75W-80 GL-4

### Combisynt Special Gear Oil

#### DESCRIPTION

**DEUTSCHÖL 75W-80 GL-4** is a High-performance gear oil based on high-quality fully synthetic and HC synthetic components, in combination with advanced additive technology. Suitable for use in modern manual and transaxle transmissions. Please note: Not suitable for use in stepped automatic transmissions, DCT/DSG transmissions or CVT transmissions

#### THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 75W-80  
API GL-4,  
Truck:  
DAF, Eaton,  
MAN 341 VR, MAN 341 Z4,  
MB 235.29, Voith Retarder,  
Volvo 97307

Passenger car:

Alfa Romeo, BMW, Dacia, Fiat, Honda, Mercedes Benz, Mini  
PSA (Citroen, Peugeot), Renault, Seat, Skoda, Smart, Volvo,  
VW -

Where the viscosity of 75W-80 and the performance of API  
GL4 are required..

#### TYPICAL CHARACTERISTICS

##### Properties

Density at 15°C  
Pourpoint  
Viscosity at 40 °C  
Viscosity at 100 °C  
Viscosity Index

##### Testing according

DIN 51757  
DIN ISO 3016  
DIN 51562  
DIN 51562  
DIN ISO 2909

##### Data Unit

0,858 g/ml  
< -40 °C  
54 mm<sup>2</sup>/sec  
9,5 mm<sup>2</sup>/sec  
161



Contains Long-chain alkyl amine. May produce an allergic reaction.



Article number: 4777580

## AVAILABLE PACKAGING



Item-number: 4777580-1



4777580-4



4777580-5



4777580-20



Item-number: 4777580-60



4777580-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.