

Article number: 4000011

ATF 600 EU

Automatic Transmission Fluid

DESCRIPTION

DEUTSCHÖL ATF 600 EU covers a wide range of possible applications, especially for vehicles from European manufacturers. Suited for life time application (please observe manufacturer's instructions) in automatic gear boxes, hydrostatic drives and power steering units.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

Dexron VI, Dexron III, Dexron II	(100°C Viscosity by Dexron III level adjusted)
Bentley	P/N PY112995PA
Jaguar	Fluid 8432, JLM 20238, 20292, 21044, KI7, WSS-M2C922-AI
Land Rover	P/N TYK500050, P/N LR0022460: LV
Maserati	P/N 231603
PSA (Peugeot, Citroën)	P/N Z 000169756
PSA / Opel	Asian AW-I, Dexron VI, III H, III G, II E, II D, II, Type A SuffixA P/N 12378515 [Synthetic], P/N 19 40 700/767 P/N 21005966 Transaxle, P/N 22717466 P/N 88863400/401, P/N 88900925, P/N 9985010 [PSF], P/N 9986195, T-IV
Renault	Matic D2
Volvo	P/N 1161521, P/N 1161540 / 1161640 1273,4l [Volvo Constr. Equip. (VCE)]
SAAB	3309-T-IV.93165 147-AW-I

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
------------	-------------------	------	------



Density at 15°C
 Pourpoint
 Viscosity at 40 °C
 Viscosity at 100 °C
 Viskosity Index

Article number: 4000011

DIN 51757 0,849 g/ml
 DIN ISO 3016 < -45 °C
 DIN 51562 34 mm²/sec
 DIN 51562 6,95 mm²/sec
 DIN ISO 2909 170

AVAILABLE PACKAGING



Item-number:..

4000011-1

4000011-4

4000011-5

4000011-20



Item-number:

4000011-60

4000011-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.

