

Article number: 1081231

15W-30 UTTO Megafarm 15W-30 UTTO

Tractors Hydrofluid

DESCRIPTION

DEUTSCHÖL 15W-30 UTTO Megafarm is a Tractor fluid with outstanding multipurpose characteristics for agricultural tractors and industrial machines. It can be used as hydraulic oil as well as transmission oil, including wet brakes and clutches.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

SAE 15W-30
DIN 51524 HVLP, API GL-4, MIL-L-2105
Allison C4, Caterpillar TO-2
Case New Holland MAT 3525, 3526
Ford M2C 134D, M2C 48-C2
John Deere J20 C
Massey Ferguson CMS M1135, M1143, M1145

Komatsu 806-0002
Sperry Vickers / Eaton I-280-S
New Holland 410B, 420A,
Volvo WB 101, 97303
ZF TE-ML 03E, 05E, 06A*, B*, C*, 07B
(*excluding latest demand from 100h KRL-Test)

TYPICAL CHARACTERISTICS

Properties	Testing according	Data	Unit
Density at 15°C	DIN 51757	0,875	g/ml
CCS -20 °C	ASTM-D 5293	5500	cP
Pourpoint	DIN ISO 3016	< -25	°C
Viscosity at 40 °C	DIN 51562	80	mm ² /sec
Viscosity at 100 °C	DIN 51562	11	mm ² /sec
Viscosity Index	DIN ISO 2909	125	

Article number: 1081231

AVAILABLE PACKAGING

 1L

Item-number: 1081231-1

 4L

1081231-4

 5L

1081231-5

 20L

1081231-20

 60L

Item-number:

1081231-60

 205L

1081231-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.