

Article number: 6110255

Holzspalteröl

Hydraulic Oil for Wood Splitters

DESCRIPTION

DEUTSCHÖL Holzspalteröl suitable for use in wood splitters under hardest environmental conditions. The fast build-up of pressure also conditions as well as very good water and air separation properties guarantee failure-free operation with minimum wear characteristics.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:







ISO VG 22, 32, 46
DIN 51524 Teil 3 (85-06) with better cold behaviour

TYPICAL CHARACTERISTICS

Properties	Testing according	22	32	46	Unit
Density 15°C	DIN 51757	0,859	0,860	0,860	g/ml
Pourpoint	DIN ISO 3016	< -32	< -30	< -28	°C
Viscosity 40 °C	DIN 51562	22	32	46	mm ² /sec
Viscosity 100 °C	DIN 51562	4,4	5,6	7,1	mm ² /sec
Flashpoint	DIN ISO 2592	190	195	205	°C

Article number: 6110255

AVAILABLE PACKAGING

Item-Number						
VG 110	6110255-1	6110255-4	6110255-5	6110255-20	6110255-60	6110255-205
VG 150	6110355-1	6110355-4	6110355-5	6110355-20	6110355-60	6110355-205
VG 46	6110455-1	6110455-4	6110455-5	6110455-20	6110455-60	6110455-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.