

Article number: 6220655

## HLP Special Hydraulic Oil

### DESCRIPTION

**DEUTSCHÖL HLP Special Hydraulic oils** are practice-proven lubricants, based on API Group II base oils. This product ensures an outstanding viscosity temperature behaviour and improved oxidation stability

**THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:**

ISO VG 15, 22, 32, 46, 68, 100, 150  
DIN 51524 Teil 2 (85-06)  
CETOP RP 91 H  
Denison Filterability TP 02100  
VDMA 24318


Hoesch HWN 2333  
SEB 181 222, SIS SS 155434  
Sperry Vickers I-286-S  
Thyssen TH N-256 132  
U.S. Steel 126 u. 127

### TYPICAL CHARACTERISTICS

Properties	Testing according	HLP 15	HLP 22	HLP 32	HLP 46	HLP 68	HLP 100	HLP 150	Unit
Density 15°C	DIN 51757	0,858	0,86	0,86	0,865	0,87	0,88	0,885	g/ml
Pourpoint	DIN ISO 3016	-32	-30	-28	-25	-23	-22	-20	°C
Viscosity 40 °C	DIN 51562	15	22	32	46	68	100	150	mm <sup>2</sup> /sec
Viscosity 100 °C	DIN 51562	3,4	4,3	5,4	6,8	9	11,5	15	mm <sup>2</sup> /sec
Flashpoint	DIN ISO 2592	180	185	195	212	220	225	230	°C

Article number: **6220655**

## AVAILABLE PACKAGING

Item-Number	 1L	 4L	 5L	 20L	 60L	 205L
HLP 15	6220195-1	6220195-4	6220195-5	6220195-20	6220195-60	6220195-205
HLP 22	6220255-1	6220255-4	6220255-5	6220255-20	6220255-60	6220255-205
HLP 32	6220355-1	6220355-4	6220355-5	6220355-20	6220355-60	6220355-205
HLP 46	6220455-1	6220455-4	6220455-5	6220455-20	6220455-60	6220455-205
HLP 68	6220655-1	6220655-4	6220655-5	6220655-20	6220655-60	6220655-205
HLP 100	6220805-1	6220805-4	6220805-5	6220805-20	6220805-60	6220805-205
HLP 150	6221505-1	6221505-4	6221505-5	6221505-20	6221505-60	6221505-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.