

Article number: 6550355

HVLP-D

Multifunctional Hydraulic Oil

DESCRIPTION

DEUTSCHÖL HVLP-D Hydraulic oils are detergent oils with superior cleaning performance.

This product absorbs general contaminations and water. An improved viscosity temperature behaviour as well as advanced wear protection properties ensure a permanent operation at medium-pressure and at increased operating temperatures.

THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:

ISO VG 32, 46, 68, 100

DIN 51524 Teil 3 (85-06 excl. demulsify behaviour)

ISO VG 32, 46, 68, 100

DIN 51524 Teil 3 (85-06 excl. demulsify behaviour)

TYPICAL CHARACTERISTICS

| Properties | Testing according | HVLP 32 | HVLP 46 | HVLP 68 | HVLP 100 | Unit |
|------------------|-------------------|------------|------------|------------|-------------|----------------------|
| Density 15°C | DIN 51757 | 0,86 | 0,865 | 0,87 | 0,875 | g/ml |
| Pourpoint | DIN ISO 3016 | -30 | -27 | -24 | -22 | °C |
| Viscosity 40 °C | DIN 51562 | 32 | 46 | 68 | 100 | mm ² /sec |
| Viscosity 100 °C | DIN 51562 | 6,3 | 8,2 | 11 | 15 | mm ² /sec |
| Flashpoint | DIN ISO 2592 | 185 | 200 | 210 | 215 | °C |
| VKA 20h | DIN 51350-6 | <15 | <16 | <16 | <16 | % |

Article number: **6550355**

AVAILABLE PACKAGING

| Item-Number |  1L |  4L |  5L |  20L |  60L |  205L |
|-------------|--|--|--|--|---|--|
| HVLPD D32 | 6550355-1 | 6550355-4 | 6550355-5 | 6550355-20 | 6550355-60 | 6550355-205 |
| HVLPD D46 | 6550455-1 | 6550455-4 | 6550455-5 | 6550455-20 | 6550455-60 | 6550455-205 |
| HVLPD D88 | 6550655-1 | 6550655-4 | 6550655-5 | 6550655-20 | 6550655-60 | 6550655-205 |
| HVLPD D100 | 6550805-1 | 6550805-4 | 6550805-5 | 6550805-20 | 6550805-60 | 6550805-205 |

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.