

Article number: 3001605

## CL Machine Oil

### DESCRIPTION

**DEUTSCHÖL CL** according to DIN 51517-2 CL, also suitable as circulating and hydraulic oil as well as for lubrication of roller and sliding bearings, due to no tendency towards gumming. It is neutral towards non-ferrous metals and usual sealing materials.

**THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:**

ISO VG 68, 100, 150, 220







ISO VG 68, 100, 150, 220

### TYPICAL CHARACTERISTICS

Properties	Testing according	CL 68	CL 100	CL 150	CL 220	Unit
Density 15°C	DIN 51757	0,875	0,880	0,885	0,887	g/ml
Pourpoint	DIN ISO 3016	< -20	< -18	< -15	< -12	°C
Viscosity 40 °C	DIN 51562	68	100	150	220	mm <sup>2</sup> /sec
Viscosity 100 °C	DIN 51562	9	11,5	15	19	mm <sup>2</sup> /sec
Flashpoint	DIN ISO 2592	230	235	240	245	°C

Article number: 3001605

## AVAILABLE PACKAGING

Item-Number	 1L	 4L	 5L	 20L	 60L	 205L
CL 68	3000655-1	3000655-4	3000655-5	3000655-20	3000655-60	3000655-205
CL 100	3000805-1	3000805-4	3000805-5	3000805-20	3000805-60	3000805-205
CL 150	3001205-1	3001205-4	3001205-5	3001205-20	3001205-60	3001205-205
CL 220	3001605-1	3001605-4	3001605-5	3001605-20	3001605-60	3001605-205

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.