

Article number: **1098740**

## 8006 HP Power Generator

### Gas Motor Oil Low Ash

#### DESCRIPTION

**DEUTSCHÖL 8006 Power Generator** is a proven gas engine oil with a low ash content and special power reserves suitable for many gas engines with catalytic converter operation. Selected components are the basis for good wear and corrosion protection, high acid neutralization capacity and excellent oxidation and temperature stability.

**THIS PRODUCT IS RECOMMENDED BY DEUTSCHÖL IF THE FOLLOWING FILLING REQUIREMENTS ARE REQUIRED:**

SAE 40  
MTU Category I  
PERKINS GAS ENGINE OIL - NATURAL GAS GE JENBACHER TI 1000-1109  
MWN TR 0199-99-2105/7, Lube Oils for Gas Engines  
MAN 3271-2

WARTSILA 34SG, WARTSILA 32 DF  
WARTSILA 28SG, WARTSILA 220 SG  
WARTSILA NSD W25SG,  
WARTSILA NSD W12V150SG,  
WARTSILA NSD W12V175SG  
WARTSILA NSD W12V175SG

#### TYPICAL CHARACTERISTICS

##### Properties

Density at 15°C

Pourpoint

Viscosity at 40 °C

Viscosity at 100 °C

Viscosity Index

Base Number (TBN)

Sulphated ash

##### Testing according

DIN 51757

DIN ISO 3016

DIN 51562

DIN 51562

DIN ISO 2909

ASTM-D 2896

ASTM D 874

##### Data Unit

0,858 g/ml

&lt; -20 °C

120 mm<sup>2</sup>/sec13,5 mm<sup>2</sup>/sec

109







6,0 mgKOH/g

0,5 %



Article number: 1098740

## AVAILABLE PACKAGING

				
Item-number:	1098740-1	1098740-4	1098740-5	1098740-20
				
Item-number:	1098740-60	1098740-205		

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.