

Article number: 921041

HIGHTEC ANTIFREEZE READY MIX -25°C

DESCRIPTION

DEUTSCHÖL HIGHTEC ANTIFREEZE READY-MIX -25 °C is a premium radiator antifreeze ready-mix free of nitrite, amine and phosphate (ready to use). It reliably protects against deposits, corrosion and foam in cast iron and aluminium engines in accordance with the manufacturer's instruction..

Application

DEUTSCHÖL HIGHTEC ANTIFREEZE READY-MIX -25 °C has been developed to meet the requirements of aluminium and cast iron engines. It reliably protects against deposits, corrosion and foam formation and thus ensures optimal heat dissipation. It is used in many internal combustion engines according to the manufacturer's specification. HIGHTEC ANTIFREEZE READY-MIX -25 °C can be used immediately and provides reliable protection at temperatures as low as -25°C without further dilution.

The quality of this product is equivalent to EU regulations

- ASTM D3306/D4985
- SAE J1034

Additionally this product is recommended when the following filling instructions are required

- JIS K 2234
- Erfüllt die Korrosionsschutzanforderungen der / Meets corrosion protection requirements of VW TL 774-C (G11)

Article number: 921041

Benefits

- Ready-mix - ready for immediate use
- Reliable antifreeze protection at temperatures as low as -25°C
- Elimination of problems caused by unsuitable water quality or a false mixing ratio
- Available for use in cast iron and aluminium engines
- Prevention of deposits in a reliable manner
- Very good and permanent corrosion protection
- Unsurpassed protection against cavitation
- Minimal tendency to foam
- Miscible and compatible with other antifreeze agents of the same specification. However, in order to exploit the full product benefits of HIGHTEC ANTIFREEZE READY-MIX -25 °C, a complete coolant change is recommended.

Property	Method	Unit	Value
Density at 20 °C	ASTM D1122	g/ml	1.07
Color	visuell	-	blau / blue
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	> 100
Boiling point	ASTM D 1120	°C	104
Ph	ASTM D1287	-	7,8-8,5
Freezing point 1:1 AF:Water	ASTM D1177	°C / °F	-25/ -13

Article number: 921041



Item-number:..

921041-15

921041-5

921041-20



Item-number:

921041-60

921041-200

921041-1000

The information in this product data sheet is based on years of experience of our team and our partners. Our professional competence in the development and manufacturing of lubricants are based on the current state-of-the-art. Universally valid statements regarding the function of our lubricants are not possible, because the lubricant performance can be influenced by a series of factors. As a result, the lubricant filling process, the exact purpose of use, the general operating conditions, the system degree of wear and the system contamination etc. must be taken into account in particular in engines, machinery and equipment. The data given in this product data sheet represents general, non-binding guideline values. No warranty expressed or implied is given concerning the properties. We recommend to consult our team regarding the application conditions and requirements before the DEUTSCHÖL lubricant is used. The user should test the functional suitability of our lubricants in the intended application and use the product with the corresponding care and responsibility according to the manufacturer's specifications. Our products undergo continuous improvements. We therefore reserve the right to change our product program, the products and their manufacturing processes as well as all details at any time and without warning. Please note: Our products may not be used in aircraft and spacecraft or parts thereof.