

HOTPLATE

specification



| | Model | SH-5C | SH-6C | SH-7C | SH-8C | SH-9C |
|-------------------|--------------------------|--------------------------------------|-------------|-------------|-------------|-------------|
| Structure | Working time | Continuous | | | | |
| | Max temp. (℃) | 350℃ | | | | |
| | Outer shell | Iron plate welding, surface spraying | | | | |
| | Hot plate | Aluminium tensile | | | | |
| | Driving mode | No | | | | |
| | Heating power(W) | 1200 | 1800 | 2000 | 2600 | 3000 |
| Controller | Continuous operation | Yes | | | | |
| | Setting Method | Digital | | | | |
| | Timer | Digital | | | | |
| | Operation function | No | | | | |
| | Temperature asensor | K model | | | | |
| | Exterior size (W*L*H mm) | 340*370*220 | 420*500*220 | 450*470*220 | 420*650*220 | 470*650*220 |
| | Plate size (mm) | 300*300 | 350*450 | 400*400 | 350*600 | 400*600 |
| | Plate load (KG) | 20 | 30 | 30 | 38 | 40 |
| | Power supply (50/60Hz) | 220V | | | | |
| | NW/GW (KG) | 6.2 / 7 | 8.4 / 9.6 | 8.5 / 9.8 | 11/13/2018 | 12 / 14.2 |