

# HandyCHECKPOINT™

This multi-function sentry device will make your facility safer by checking who can access and if they are well. Accurate temperature checks and compliance with wearing of a mask, will reduce queues and speed up entry into your premises.



## Checkout these 10 key features

- 1) Best Artificial Intelligence Multi Function Thermal Detector in marketplace.
- 2) Fastest temperature recording (50ms) with mask detection in under 0.3 seconds
- 3) Audible alerting in male or female voice:
  - high temperature
  - need to wear mask
  - welcome message
  - + moreAll customisable in .wav file format
- 4) Email alerting, forwards an image and data to contact, or distribution list using branch server and HandyCHECKPOINT Manager (Cloud Service).
- 5) Facial Recognition combines with access control for fast touchless authorised entry, accuracy 99.9%
- 6) Time and Attendance, recording timed activity.
- 7) PC based Console Software to configure all devices, sync staff information and reporting, supplied FOC.
- 8) Integrate with your existing software using our API to pass data to your HR/Payroll systems.
- 9) Great service, 2 year warranty, optional maintenance plan.
- 10) Networking connectivity, using Ethernet, or WiFi. Web accessible setup and video streaming capability.

*Roadmap – Currently in development:  
Cloud based Enterprise Management solution, integration  
Samsung's MagicINFO for Occupancy Management.*

***“A safe and healthy workplace.  
Protect your Customers and Staff alike”***



Desktop      Child Stand      Adult Stand

**HANDY**  
Inspiration meets technology

## Technical Specification

Operation System	Linux
Display	7-inch TFT Screen
Speaker	Voice Prompt
Language	Customizable Multi-languages: English, French, Spanish, Italian, Russia, Japanese, Korean, etc.
Facial Records	Up to 50,000
Verification & Identification Speed	< 200ms
Facial Anti Spoofing	Printed photo, Electronic display of a facial photo, Replaying video, 3D face masks, etc.
Facial Recognition Accuracy Rate	99.9%
Forehead Thermometer Speed & Accuracy	<50ms, ±0.2°C
Work Range	0.3m~1.2m, 30cm~120cm
Transaction Storage	8GB EMMC storage supporting 50,000 events
Infrared thermography Camera	Uncooled Infrared focal plane junction detectors Array sensor resolution: 120*90
Facial Recognition Camera	Dual 1080p Starlight CMOS sensors for visible light and near infrared light
Communication	HTTPS, RTSP, TCP/IP, USB-Host, USB-Client and WiFi
Interface for Access Control	3rd Party Electric Lock, Exit Button, Alarm
Power Supply	12V DC, 2A (9-16V DC)
Operating Temperature	-40 °C~ 60 °C
Dimensions	120mm*226.5mm*33.5mm
Warranty	2 years return to base warranty

Distributor/Partner: