7" HD QUAD VIEW MONITOR 7QMHD







Features

- +7"HD Digital TFT-LCD Touch Screen QUAD
- + Resolution :1024 x 3 RGB x 600
- + Touch Screen Control, IR Remote Control
- + Slim Housing Rugged Design
- + PAL/ NTSC/ FLIP/ MIRROR Mode
- + Reverse cursor with on-off mode switch available + Supports 4 CH X 1080P / 720P Cameras, PAL / NTSC
- + Auto Scan with scan time selectable between 1-60s
- + Power DC 10~32V
- + Support HDMI Input and Audio Input
- + Touch Screen recognize left or right side swipe to realize channel switching + Multiple Video Formats available:PAL/NTSC/AHD,HD-TVI,HD-CVI, 720P /1080P

7"HD Colour TFT-LCD

+ Robust, Reliable & Versatile



7QMHD is a 7" High Definition Colour TFT-LCD Touch Screen Quad View Monitor.

It offers High Definition picture quality in a rugged slim housing. It supports 4 Channel at 1080P / 720P Cameras, PAL/NTSC, HDMI and Audio Input, DC 10-32V automatic power, Parking guide line display On/Off and automatic dimmer function.

7QMHD is supplied with the following: Sun Shield, Adjustment U Bracket & Screws, Base Mount Bracket, IR Remote Control, Multiple Cable.

The 7QMHD is a High Quality Compact camera.



Specifications



LCD Size Video System Resolution LCD Brightness Screen Mode Field of View **Colour Configuration** Parking Line

Dimmer

Camera Input Audio input Triggers Display Mode

Audio Output Speaker Impedance Housing Material Vibration Rating Camera Connector OSD Language

Power Input Operating Temp Weight

NTSC /PAL /SECAM Automatic Detection 1024 x RGB x 600 500cd/m2 16:9 Wide Screen Top 50° / Bottom 70° / Left 70° / Right 70° **RGB Strip** Auto Display by a Trigger, Parking Line Adjustable Óption Auto Brightness Adjustable by CDS Sensor or Manual 4 Cameras, 1 HDMI, 1 VGA, 1 DVR 4 Cameras 1 VGA, 1 DVR 5 Channel Display of Auto Trigger 5 Pin Full (Normal or Mirror View Selectable) Camera CH Scan 1W Mono Speaker 16 Ohm **Touch Neutral Black** 7G with U –support bracket 4 Pin Mini-DIN with Metal Screw Lock 9 Multi English, French, Spanish, Dutch, Italian, German

DC 10-32V Automatic Power

-20°C ~ + 70°C

1.60 Kg



