

Features

- 1/2.8" SONY Starvis HD CMOS Sensor
- Full 1080P (1920 x 1080) 30P
- Marine IR Bullet Camera
- 316L Stainless Steel
- 2.8 ~ 12mm Motorized Lens / UTC Control
- Built-in Smart IR LEDs 30M Distance
- Weather Proof to IP67 Rated
- Ultra High Sensitivity Camera
- Supports D-WDR, Defog, 2D+3DNR
- True Day & Night / True Wide Dynamic Range
- Format AHD, HD-TVI, HD-CVI, CVBS



Specification	CSP-MHD-SS
Image Sensor	Sony 1/2.8" Starvis CMOS Sensor
Effective Pixels	1945 H x 1097 V 2.13 Megapixels
Scanning System	Progressive Scan
Focal Length	2.8 ~ 12 mm Motorized Lens / F1.4
Angle of View	D: 138.0° W ~ 40.0° T / H: 103.0° W ~ 30.8° T / V: 74.4° W ~ 23.3° T
Min. Illumination	Colour: 003 Lux, B/W : 0 Lux (IR LED On)
IR LED	IR LED / 30M Distance
Wide Dynamic Range	Off / On
Day & Night Mode	True Day & Night (Auto, Colour, BW)
Resolution	1920 x 1080, 1440 x 1080, 1280 x 1024 / 720, 1024 x 768 800 x 600 / 480, D1, 640 X 480, 400 x 240, CIF
Frame Rate	Max 30 / 25fps (NTSC / PAL)
Streaming	Dual Stream : Main Stream (1080p) & Sub Stream (D1)
Video Codec	Simultaneous Multi-Codec (H.264 / H.265 / MJPEG)
Bitrate Control	CBR / VBR, Network Bandwidth Control
Connection Mode	Fixed OP, DHCP, DDNS
Security	WS-Security, RTSP Access Control
Connection	Ethernet 10/100/1000base - T (RJ-45)
Network Protocol	TCP / IP, HTTP, RTP / RTSP, UDP, DHCP, FTP SMTP, NTP, ARP, ICMP, DDNS, ONVIF
ONVIF	Support (Profile-S)
Input Power	PoE Class 3 (IEEE 803.3af)
IP Rated	Weather proof to IP67 Rated
Material	316L Stainless Steel / Electro-Polished
Operating Temp	-25°C ~ +55°C
Dimension	99.2 W x 138.2 H x 164 L mm
Net Weight	2.0K Kg

Dimensions

