

Features

1/3" Double Scan Super HAD CCD II

Micro Marine IR Dome Camera

650 TV Lines

Outstanding Picture Quality

Robust, Reliable & Versatile

Built-in Smart IR LEDs

Weather Proof to IP66 Rated

IR Distance 10M

2D DNR Digital Noise Reduction

Quick & Easy to install

Anti Corrosion & Salt Resistant Cameras



| Specification | CSP-MIRO |
|-------------------|--|
| Image Sensor | 1/3" Double Scan Super HAD CCD II |
| Effective Pixels | NTSC: 976 H x 494 V / PAL: 976 H x 582 V |
| H. Resolution | 650TV Lines |
| Scanning System | NTSC: 525 Lines, PAL : 625 Lines. 2:1 Interlaced |
| Sync System | Internal |
| Frequency | NTSC : Horizontal 15.732KHz / Vertical 59.94KHz PAL : Horizontal 15.625KHz / Vertical 50KHz |
| Video Output | 1.0Vp-p Composite 75 Ω Composite |
| S/N Ratio | More than 52dB (AGC Off) |
| Min. Illumination | 0.1 Lux, |
| Shutter Speed | NTSC (1/60 ~1/100,000 sec, PAL 1/50 ~ 1/100,000 sec |
| Gamma Correction | Y + 0.45 |
| White Balance | 1,800°K ~ 10,500°K |
| Gain Control | 6dB / 12dB / 18dB / 24dB / 30dB / 36dB / 42dB / 44.8dB |
| WDR | Double Shutter + ATR-EX2 |
| Smear Effect | 0.01% |
| Lens | 3.7mm Fixed Lens |
| Day & Night | Auto |
| IR LED's | 10m Distance |
| Power Source | 12V DC |
| Operating Current | 90mA |
| Operating Temp | -10°C to + 50°C |
| Humidity | 0% to 80% RH |
| Dimension | Dia 50.5 mm x H 44mm |
| Net Weight | 250g |

Dimensions

