

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0Page: 1/9
(30751172/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Dehypon® LS 54 Flex

Recommended use of the chemical and restriction on use

Recommended use*: Raw material

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms: Fatty Alcohols, C12-14, Ethoxylated, Propoxylated

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Hazard Statement:

H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 2/9
(30751172/SDS_GEN_US/EN)

Precautionary Statements (Prevention):
P273 Avoid release to the environment.

Precautionary Statements (Disposal):
P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
68439-51-0	>= 75.0 - <= 100.0%	Alcohols, C12-14, ethoxylated propoxylated

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Keep patient calm, remove to fresh air.

If on skin:
Wash thoroughly with soap and water. If irritation develops, seek medical attention.

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open.

If swallowed:
Rinse mouth and then drink plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms: No significant symptoms are expected due to the non-classification of the product.

Indication of any immediate medical attention and special treatment needed

Note to physician
Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 3/9
(30751172/SDS_GEN_US/EN)

Suitable extinguishing media:
water spray, dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

harmful vapours, carbon oxides

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures see, section 8.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

No special measures necessary provided product is used correctly.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Stove-lacquer RDL 50, Stainless steel 1.4301 (V2), Stainless steel 1.4306 (V2A), Stainless steel 1.4361, Stainless steel 1.4401, Stainless steel 1.4439, Stainless steel 1.4539, Stainless steel 1.4541, Stainless steel 1.4571

Further information on storage conditions: Keep container tightly closed and dry; store in a cool place.

Storage stability:

Storage temperature: ≤ 70 °C

The packed product is not damaged by low temperatures or by frost. Bulk must be protected from solidification.

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 4/9
(30751172/SDS_GEN_US/EN)

Protect from temperatures above: 70 °C
Properties of the product change irreversibly on exceeding the limit temperature.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:
Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Breathing protection if breathable aerosols/dust are formed.

Hand protection:
Chemical resistant protective gloves

Eye protection:
Wear face shield or tightly fitting safety goggles (chemical goggles) if splashing hazard exists.

Body protection:
No body protection required if used for intended purpose and satisfying generally accepted industrial hygiene rules.

General safety and hygiene measures:
Wear protective clothing as necessary to minimize contact. Handle in accordance with good industrial hygiene and safety practice. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
Odour threshold:	not determined	
Colour:	yellowish	
pH value:	6.0 - 7.5 (1 %(m))	(DIN EN 1262)
pour point:	-10 °C	(DIN ISO 3016)
solidification point:	< 5 °C	(DIN ISO 2207)
Boiling point:	> 250 °C	
Sublimation point:	No applicable information available.	
Flash point:	approx. 200 °C	(DIN ISO 2592)
Flammability:	not flammable	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 300 °C	
Vapour pressure:	< 0.1 hPa	
Density:	approx. 0.97 g/cm ³ (20 °C)	(DIN 51757)

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 5/9
(30751172/SDS_GEN_US/EN)

	approx. 0.94 g/cm ³ (70 °C)	(DIN 51757)
Relative density:	No data available.	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 300 °C	
Viscosity, dynamic:	< 20 mPa.s (60 °C)	(DIN EN 12092)
	approx. 60 mPa.s (23 °C)	(DIN EN 12092)
Viscosity, kinematic:	No applicable information available.	
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	soluble	
Solubility (qualitative):	soluble	
	solvent(s): Ethanol,	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.
The product is chemically stable.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

acids, Alkalines, caustics, halogens, reactive chemicals

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
> 300 °C

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 6/9
(30751172/SDS_GEN_US/EN)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: May be harmful if swallowed in large quantities. May cause respiratory irritation.

Oral

Type of value: LD50
Species: rat (male/female)
Value: > 2,000 - 5,000 mg/kg (OECD Guideline 401)

Inhalation

Type of value: LC50
Species: rat
not determined

Dermal

Type of value: LD50
Species: rat
Value: > 5,000 mg/kg

Irritation / corrosion

Assessment of irritating effects: Not irritating to the eyes. Skin contact causes slight irritation.

Skin

Species: rabbit
Result: Slightly irritating.
Method: OECD Guideline 404

Eye

Species: rabbit
Result: non-irritant
Method: Draize test

Sensitization

Assessment of sensitization: No sensitizing effect.

Guinea pig maximization test

Species: guinea pig
Result: Non-sensitizing.
Method: OECD Guideline 406

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated oral uptake of the substance did not cause substance-related effects.

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 7/9
(30751172/SDS_GEN_US/EN)

Genetic toxicity

Assessment of mutagenicity: Based on available Data, the classification criteria are not met.
Genetic toxicity in vitro: OECD Guideline 471 Ames-test S. typhimurium, E. coli:negative

Carcinogenicity

Assessment of carcinogenicity: No data available concerning carcinogenic effects.

Reproductive toxicity

Assessment of reproduction toxicity: No data available.

Teratogenicity

Assessment of teratogenicity: No data available.

Symptoms of Exposure

No significant symptoms are expected due to the non-classification of the product.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely toxic for aquatic organisms. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to fish

LC50 (48 h) > 1 - 10 mg/l, Leuciscus idus (DIN 38412 Part 15)

Aquatic invertebrates

EC50 (24 h) > 1 - 10 mg/l, Daphnia magna (OECD Guideline 202, part 1)

Aquatic plants

EC50 (72 h) > 1 - 10 mg/l (growth rate), Desmodemus subspicatus (OECD Guideline 201)
acute Effect

EC10 (72 h) > 0.1 - 1 mg/l (growth rate), Desmodemus subspicatus (OECD Guideline 201)
long-term effect

Chronic toxicity to fish

No data available.

Assessment of terrestrial toxicity

No data available concerning terrestrial toxicity.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

OECD Guideline 209 bacterium/EC0: > 100 mg/l

DIN 38412 Part 8 bacterium/EC0: > 100 mg/l

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 8/9
(30751172/SDS_GEN_US/EN)

Readily biodegradable (according to OECD criteria).

Elimination information

> 60 % (28 d) (OECD 301F; ISO 9408; 92/69/EEC, C.4-D) Readily biodegradable (according to OECD criteria).

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.
Adsorption to solid soil phase is possible.

Additional information

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Safety Data Sheet

Dehypon® LS 54 Flex

Revision date : 2017/12/05
Version: 3.0

Page: 9/9
(30751172/SDS_GEN_US/EN)

<u>CERCLA RQ</u>	<u>CAS Number</u>	<u>Chemical name</u>
1000 LBS	75-07-0	acetaldehyde
100 LBS	75-56-9; 107-18-6; 123-91-1	Propylene oxide; 2-propen-1-ol; 1,4-dioxane
10 LBS	75-21-8	Ethylene Oxide

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

[Other Prop 65 components may be present in the product.]

NFPA Hazard codes:

Health: 1 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 1 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2017/12/05

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Dehypon® LS 54 Flex is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET