

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05

Version: 3.0

Page: 1/10

(30149367/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Lutensol® XP 70

Recommended use of the chemical and restriction on use

Recommended use*: Raw material for the chemical-technical industry
Suitable for use in industrial sector: chemical industry

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: Polymer
Synonyms: Ethoxylated Alcohol

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Tox.	4 (oral)	Acute toxicity
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Aquatic Acute	3	Hazardous to the aquatic environment - acute

Label elements

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 2/10
(30149367/SDS_GEN_US/EN)

Pictogram:



Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H302	Harmful if swallowed.
H402	Harmful to aquatic life.

Precautionary Statements (Prevention):

P280	Wear eye/face protection.
P273	Avoid release to the environment.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301 + P330	IF SWALLOWED: rinse mouth.

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Labeling of special preparations (GHS):

This classification is based on the current CESIO recommendations. This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request or at the request of a detergent manufacturer.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
160875-66-1	>= 75.0 - <= 100.0%	Poly(oxy-1,2-ethanediyl), .alpha.-(2-propylheptyl)-.omega.-hydroxy-

4. First-Aid Measures

Description of first aid measures

General advice:

Remove contaminated clothing.

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 3/10
(30149367/SDS_GEN_US/EN)

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., (Further) symptoms and / or effects are not known so far

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.
------------	---

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Further accidental release measures:

High risk of slipping due to leakage/spillage of product.

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Information regarding personal protective measures, see section 8.

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 4/10
(30149367/SDS_GEN_US/EN)

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with absorbent material (e.g. sand, sawdust, general-purpose binder).

Dispose of absorbed material in accordance with regulations.

For large amounts: Pump off product.

Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling

No special measures necessary provided product is used correctly.

Protection against fire and explosion:

No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Stainless steel 1.4301 (V2), Stainless steel 1.4306 (V2A), Stainless steel 1.4361, Stainless steel 1.4401, Stainless steel 1.4439, Stainless steel 1.4539, Stainless steel 1.4541, Stainless steel 1.4571, Stove-lacquer RDL 50

Further information on storage conditions: Keep container tightly closed and in a cool place.

Storage stability:

Storage temperature: $\leq 70\text{ }^{\circ}\text{C}$

The packed product is not damaged by low temperatures or by frost. Bulk must be protected from solidification.

Protect from temperatures above: $70\text{ }^{\circ}\text{C}$

Properties of the product change irreversibly on exceeding the limit temperature.

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate. Breathing protection if breathable aerosols/dust are formed.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05

Version: 3.0

Page: 5/10

(30149367/SDS_GEN_US/EN)

General safety and hygiene measures:

Wearing of closed work clothing is required additionally to the stated personal protection equipment. No eating, drinking, smoking or tobacco use at the place of work. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Form:	liquid	
Odour:	product specific	
Odour threshold:	not determined	
Colour:	colourless to yellowish	
pH value:	approx. 7 (50 g/l, 23 °C)	(DIN EN 1262)
solidification temperature:	approx. 9 °C	(DIN ISO 2207)
Boiling point:	not applicable	
Flash point:	approx. 130 °C	(DIN ISO 2592)
Flammability:	not self-igniting	
Lower explosion limit:	For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	> 300 °C	
Vapour pressure:	< 0.1 hPa (20 °C)	
Density:	approx. 1.00 g/cm ³ (25 °C)	(DIN 51757)
	approx. 0.96 g/cm ³ (70 °C)	(DIN 51757)
Relative density:	No data available.	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	> 350 °C (DTA)	
Viscosity, dynamic:	approx. 300 mPa.s (23 °C)	(DIN EN 12092)
	< 20 mPa.s (70 °C)	(DIN EN 12092)
	< 20 mPa.s (60 °C)	(DIN EN 12092)
Particle size:	The substance / product is marketed or used in a non solid or granular form.	
Solubility in water:	soluble	
Solubility (qualitative):	soluble	
	solvent(s): Ethanol,	
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.	
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 6/10
(30149367/SDS_GEN_US/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

The product is chemically stable.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

caustics, halogens, Alkalines, acids, reactive chemicals

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

> 350 °C (DTA)

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Oral

Type of value: LD50

Species: rat (male/female)

Value: > 300 - 2,000 mg/kg (OECD Guideline 423)

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

Irritation / corrosion

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 7/10
(30149367/SDS_GEN_US/EN)

Assessment of irritating effects: May cause severe damage to the eyes.

Eye

Moderate to severe irritation to the eyes.

Sensitization

Assessment of sensitization: Based on the structure, there is no suspicion of a skin-sensitizing potential.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The information available on the product provides no indication of toxicity on target organs after repeated exposure.

Genetic toxicity

Assessment of mutagenicity: Based on the structure, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: Based on the structure there is no suspicion of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity: Based on the ingredients, there is no suspicion of a toxic effect on reproduction.

Teratogenicity

Assessment of teratogenicity: Based on the ingredients, there is no suspicion of a teratogenic effect.

Other Information

The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., (Further) symptoms and / or effects are not known so far

12. Ecological Information

Toxicity

Aquatic invertebrates

EC50 (48 h) > 10 - 100 mg/l, Daphnia magna

Analogous: Assessment derived from products with similar chemical character.

Aquatic plants

EC50 (72 h) > 10 - 100 mg/l, Scenedesmus subspicatus

Analogous: Assessment derived from products with similar chemical character.

Chronic toxicity to fish

No observed effect concentration > 1 mg/l

Literature data.

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 8/10
(30149367/SDS_GEN_US/EN)

Persistence and degradability

Elimination information

>= 90 % Bismuth-active substance (mod. OECD 303A)

Analogous: Assessment derived from products with similar chemical character.

> 60 % CO₂ formation relative to the theoretical value (28 d) (OECD 301B; ISO 9439; 92/69/EEC, C.4-C) Readily biodegradable.

Analogous: Assessment derived from products with similar chemical character.

Bioaccumulative potential

Bioaccumulation potential

Accumulation in organisms is not to be expected.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Adsorption to solid soil phase is possible.

Additional information

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Inhibition of degradation activity in activated sludge is not to be anticipated during correct introduction of low concentrations. Do not release untreated into natural waters.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05
Version: 3.0

Page: 9/10
(30149367/SDS_GEN_US/EN)

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHYLENE OXIDE, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 0 Special:

HMIS III rating

Health: 3 Flammability: 1 Physical hazard: 0

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2019/06/05

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Lutensol® XP 70 is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED

Safety Data Sheet

Lutensol® XP 70

Revision date : 2019/06/05

Page: 10/10

Version: 3.0

(30149367/SDS_GEN_US/EN)

A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET