



9kg bags

COVERAGE:
2m² at 10mm
THICKNESS



Highly insulating thermal base layer. Measured k-value of 0.127W/mk



Fast setting and easy to use. Saving you time on installation.



Breathable - water vapour permeable.



UKCA and CE marked with A1 fire rating.



Adaptavate
Fabric First Solutions

breathAplasta thermal

REVISED 01 11 2022

Insulating plaster for solid walls.

A quick-setting, multi-coat plaster to thermally insulate solid wall properties, reducing energy bills and problems with mould and condensation.

Quick and easy way to improve your U-value

Quick setting time allows for faster completion on site. Apply up to 40mm per coat and up to 80mm per day with just 2 hours between coats.

Highly insulating thermal base layer well suited to all solid masonry walls.

Apply directly to any solid masonry external facing wall – brick, block and stone. A 50mm coat will improve the U value of a standard solid wall by around 60%.

A simple Internal Wall Insulation (IWI) system that breathes with you in your building.

A fabric first solution to reducing your energy bills for warmer walls & healthier homes.

For more information and to view or download any of our resources, including Declaration of Performance for relevant certifications, please visit adaptavate.com or scan the QR code.

- Declaration of Performance
- Safety Data Sheet
- Installation Videos
- Case studies
- Technical Data Sheet
- Installation Guides
- FAQs
- System guides



In Partnership with:



breathAplasta
thermal | universal | smooth

Adaptavate Ltd Unit 7 Vertex Business Park,
Bristol, BS16 7LB (UK) +44 (0) 1453 827800
info@adaptavate.com www.adaptavate.com

The Forge, Innishannon, Co.Cork,
Ireland. T12 W72X Tel: 021 477 6677
info@roundtowerlime.com

SUMMARY SHEET