



## Gilgen SLX Telescopic Automatic Door Operator

Specification:

The automatic (single bi sliding or biparting / bi sliding) model SLX Telescopic door operators as supplied by Access Entry Pty Ltd are to be electrically approved for 230/240v, fully housed in an extruded aluminum housing of height 140mm and width 270mm and must comply with all BCA requirements for automatic door operators.

The equipment shall incorporate the following features:

- **Drive** – Super-torque 15mm H section steel reinforced timing belt design
- **Motor** - Continuously rated brush-less, heavy duty DC motor, capable of 24 hour operation with power consumption of 280w and carry a minimum two year warranty.
- **Door Weights** – Maximum weight 2 doors at 120kg each or 4 doors at 75kg each.
- **Gear Box** - Self Lubricating fully sealed maintenance free gearbox. Minimum two year warranty.
- **Track** – 25um black anodized long life, for whisper quiet operation.
- **Actuation & Safety** –2 x IXIO-DT1 combination Radar & Infrared sensors for maximum safety/protection. Automatic reversing if obstruction during closing sequence with fully adjustable sensitivity settings.
- **Controller** - Solid state automatic self-learning microprocessor controller with Safety reverse/stop with delay including low speed, continuous retry after obstruction, prior to resuming normal operation.
- **Standard Interface ability** - Security, FIP, BMS.
- **Monitored battery backed failsafe.** As per BCA Regulations, doors drive fully open automatically on power failure/fire alarm (integration by others). Failsafe must provide up to 200 operations on power failure and or up to 2 days secure locking. Doors automatically return to original function mode when power resumes or fire signal is deactivated.
- **Door Type**  
Hanger Brackets to suit Aluminium framed doors ONLY
- **Locking**  
Electric locking – selectable option, of Failsafe or Fail-Secure, including battery backup and compliant with BCA & P2 push button for Emergency or after hours egress.  
Standard SK2 entry key switch (can be master keyed by client).
- **Special entry**  
Card reader or Swipe Card (by security contractor)
- **Control Functions**  
Standard- SK4- four position security key switch (can be master keyed by client)

**Warranties** : Access Entry/Gilgen SLX Telescopic Door Operator is to be covered by a two (2) year parts and twelve (12) month labour warranty.

**Maintenance:** The operator is to be safety inspected and maintained in accordance with AS5007-2007, i.e. three periodic log book entries per annum, by qualified technicians. Contact 1300 445 436 for safety/service program.

### HEAD OFFICE

#### Victoria

10 Network Dve  
Carrum Downs 3201  
P 03 8773 4200

#### NSW

5 Watson Rd  
Padstow 2211  
P 02 9973 6740

#### Queensland

14/37 Blanck St  
Ormeau 4208  
P 07 5551 6900

### Access Entry Pty Ltd

ABN 84 602 327 024

**24HR Service: 1300 445 436**

**Fax: 03 8773 4299**

sales@accessentry.com.au

**www.accessentry.com.au**