

Filter Elements and Cartridges













Vu-Flow specializes in many liquid filtration systems in irrigation, agriculture, livestock and industrial applications. Our products last under the toughest conditions and the built-in flushing design means you don't need to take your filter apart to clean it.

Many of our filter elements and cartridges can be flushed and reused, eliminating the need for expensive cartridge replacements. The filter cover is clear, so you'll be able to see and know when your filter needs to be flushed or you can add our automated ball valve and setup routine flushing for a truly maintenance-free filter system.



MELT BLOWN


Melt Blown (Spun) filters are made of 3-4 different layers of various pore sizes with more dirt holding capacity than pleated filters. These filters are great at removing silt, oil, dirt, rust/iron and particulates.

FLOW RATE

up to 100 GPM

KEY FEATURES

- » High dirt holding capacity
- » Broad chemical compatibility
- » Made of 100% pure polypropylene
- » Non-fiber releasing, suitable in relatively high temperatures



PRESSURE

up to 50 PSI

MAX TEMP

140°F

1 - 150 µm




PLEATED

Pleated filters have lower pressure drop due to increased surface area. They are used for removing suspended solids and are the most resistant to chemicals and bacterial growth.

up to 100 GPM

KEY FEATURES

- » More surface area than other filters
- » Reusable and washable
- » Low pressure drop design
- » Highly efficient micron removal



PRESSURE

up to 100 PSI

175°F

1 - 50 µm



ACTIVATED CARBON

Activated Carbon filters formed using extrusion process yielding the highest surface area of any filter. Removes impurities such as organic compounds, insecticides, pesticides, and other chemicals from water.

KEY FEATURES

- » Good adsorption capacity
- » Low pressure drop
- » Non-carbon releasing design
- » Can be used where water conditioner is not present
- » Prefiltration for RO sytems

Chart based on a 10 micron filter cartridge. 100 80 Pressure (PSI) 60 40 10 40 50 60 70 Flow (GPM) 🔾 1" Filter 💢 1.5" Filter 💢 2" Filter

FLOW RATE

up to 85 GPM

PRESSURE


up to 65 PSI

MAX TEMP

125°F

MICRON RATING

SUGGESTED REMOVAL RATES



*Activated Carbon removes contaminants such as: Pesticides, Insecticides, VOCs, Lead, Chlorine and Organic Substances

Micron (μ m) = a millionth of a meter or 1/1000 of a millimeter or 1/25,000 of an inch




POLY MESH

This durable polyester mesh material is chemical and bacterial resistant which makes it the perfect filter for coastal regions, lake, pond and well water..

KEY FEATURES

- » Perfect for filtering pond, lake and well water
- » Washable & Reusable
- » Resistant to bacteria growth
- » Wide range of micron levels



FLOW RATE

up to 100 GPM

PRESSURE

up to 150 PSI

MAX TEMP

120°F

15 - 700 µm




SS MESH

Stainless steel mesh is a durable material perfect for applications using higher water temperatures or coarse particles. They are used for coarser sediment particulate where extremely dirty water is being filtered and a stronger filter is needed.

KEY FEATURES

- » High temperature resistance
- » High durability and versatility
- » Washable and reusable
- » Anti-corrosive properties
- » Great for livestock and industrial uses



up to 100 GPM

PRESSURE

up to 150 PSI

220°F (Hot Water Model)

75 - 500 µm




HD MESH

The heavy duty stainless steel mesh is super durable and perfect for higher temperatures and very coarse or rocky abrasive particles.

KEY FEATURES

- » Super durable stainless steel
- » Temperature resistant
- » Very large mesh for coarse particles
- » Super abrasive resistance
- » Great for agricultural use



FLOW RATE

up to 135 GPM

PRESSURE up to 150 PSI MAX TEMP

220°F (Hot Water Model)

MICRON RATING

1200 - 4000 µm



Filter Selection Guide

	MELT BLOWN	PLEATED	ACTIVATED CARBON	POLY MESH	SS MESH	HD MESH	
Sediment							
Scale & Rust							ATES
Coarse Sand & Shell							PARTICULATES
Grit & Fine Sand							PAF
Silt							
Lead / Chlorine / VOCs							CHEMICALS
Pesticides / Insecticides							CHEN
Micron Removal Rating*	1 - 150 μm	1 - 50 μm	5-10 μm	15 - 700 μm	75 - 500 μm	1200 - 4000 μm	
Filter Life	< 12 Months	Reusable	< 6 Months	Reusable	Reusable	Reusable	SPECS
Flow Rate Range (GPM)**	up to 100 GPM	up to 100 GPM	up to 85 GPM	up to 100 GPM	up to 100 GPM	up to 135 GPM	
Chemical Resistant							
Hot Water Use							USAGE
Sediment Trapper™							
Irrigation							(0
Industrial							APPLICATIONS
Agriculture							APPLIC,
Livestock							A

^{*} Micron (μ m) = a millionth of a meter or 1/1000 of a millimeter or 1/25,000 of an inch



Four decades in the making, Vu-Flow has been one of the most trusted filter systems in America. Vu-Flow has tradition of designing and manufacturing screen and sand separator filters that exceed customers' expectations of quality and service. We not only have a team dedicated to meeting the needs of our customers today, but continue to expand our filter technologies to meet emerging water filtration needs.

^{**} Minimum flow rate for spin-down action: 1 GPM (34" and 1"), 18 GPM (112" and 2")