

Airport, auto dealership, corporate and office, education, government, healthcare, industrial and warehouse, municipal, parking, gas station and convenience stores, recreation and public venues, restaurants and hospitality, retail and grocery.











- Super bright Osram LEDs (LM-80)
- Total lamp efficiency: 120Lm/W, Ra: 80
- Instant start, no flickering, no humming sound
- Eco-friendly and no UV
- Energy saving >70%
- Long life span 50,000 hrs



Green Lighting Corp - Sydney - Australia
Suite 9, 138: 140 Elizabeth Drive, Liverpool 2170 NSW
Ph: 1300 412 270 mygreenlightingcorp.com
Australia | Phillippines | Singapore | Korea | USA | Europe






















## ECO TECHNICAL SPECIFICATIONS






Item	GLC-DL-ECO10W
Wattage	10W
Flux (Im)	950lm
Size (inch)	3 inch
PF	0.9
Efficiency (Im/w)	100Lm/W
CRI	>80
CCT (K)	3000K/4000K/5000K/6000K


1.0m	328 lx	2.47m
2.0m	82 lx	4.94m
3.0m	37lx	7.41m
4.0m	20.5lx	989m
5.0m	13lx	12.36m





Item	GLC-DL-ECO12W
Wattage	12W
Flux (Im)	1250lm
Size (inch)	4 inch
PF	0.9
Efficiency (Im/w)	100Lm/W
CRI	>80
CCT (K)	3000K/4000K/5000K/6000K


1.0m	500lx	2.50m
2.0m	125lx	5.00m
3.0m	56lx	7.51m
4.0m	31lx	10.0m
5.0m	20lx	12.50m





Item	GLC-DL-ECO20W
Wattage	20W
Flux (lm)	2407lm
Size (inch)	6 inch
PF	0.9
Efficiency (Im/w)	120lms/W
CRI	>80
CCT (K)	3000K/4000K/5000K/6000K

1.0m	936lx	2.52m
2.0m	234lx	5.04m
3.0m	104lx	7.56m
4.0m	59lx	10.08m
5.0m	37lx	12.60m





Item	GLC-DL-ECO25W
Wattage	25W
Flux (Im)	3026lm
Size (inch)	8 inch
PF	0.9
Efficiency (Im/w)	120lms/W
CRI	>80
CCT (K)	3000K/4000K/5000K/6000K

1.0m	1150lx	2.54m
2.0m	288x	5.08m
3.0m	128lx	7.62m
4.0m	72lx	10.15m
5.0m	46lx	12.69m

<b>Driver:</b> External Driver	Material: Diecast Alluminium Alloy, Powder coated, colour White
LEDs: Osram	Input Voltage: 220-240VAC
Storage Temperature: -40~+60°C	Life-span: 50,000 hours
Operating Temperature: -20~+45°C	IP Rate: IP44