



TECHNICAL DATA

• Luminaire source	LED SMD
• Luminaire system wattage*	10W ~ 24W
• Luminaire luminous flux*	1000lm ~ 2400lm
• Luminaire efficacy (avg.)	100lm/W (4000K)
• Correlated colour temperature*	3000K/4000K/5000K switchable
• Colour rendering index	Ra≥80
• Beam	110°
• Service lifetime*	>50,000h L70/B50
• Ingress protection	IP54
• Power factor	≥0.9
• Operating voltage	200-240V AC, 50/60Hz
• Operating temperature	-20°~45°C
• Protection class	II
• Finish	White trim (RAL9016), others on request
• Construction	Aluminium, polycarbonate
• Mounting / Cutout	Surface mounted
• Warranty*	5 years
• Luminaire termination	L/N terminal block internal termination
• Lighting control	Phase-cut dimming

ORDER DATA

Order code	Model	System wattage	Colour temperature
16333100	NOVI-250-10W-TRI-D	10W	3000K/4000K/5700K
16333101	NOVI-300-18W-TRI-D	18W	3000K/4000K/5700K
16333102	NOVI-400-24W-TRI-D	24W	3000K/4000K/5700K

FEATURES

- High efficiency, ideal fluorescent replacement
- High transparency diffuser
- Phase-cut dimmable
- IP54 weather resistant

OPTIONS/ACCESSORIES

- Colour temperature selectable; 3000K/4000K/5700K
- Other trim finishes upon request

