

MSDS

MATERIAL SAFETY DATA SHEET

ECOSORB® C-981

1. Product & Company Identification

Supplier/Manufacturer: Graver Technologies LLC Product Name: C-981

Address: 200 Lake Drive

Glasgow, Delaware 19702-3319 CAS Number: N/A U.S.A MSDS Number: 864

FAX Number: (302) 731-1707

Emergency Phone: (800) 249-1990 e-Mail: info@gravertech.com

Web Site: www.gravertech.com

Product/Material Uses: Removes color from pharmaceutical process streams.

2. Composition / Information On Ingredients

Chemical & Common Name	CAS Number	Weight Percent
Resin, Strong Base Anion Exchange	69011-15-0	20 - 40
Fiber, Cellulose	9004-34-6	20 - 40

This product contains no hazardous ingredients when evaluated by criteria established in the OSHA Hazard Communication Standard (29 CFR 1910.1200).

3. Hazards Identification

Primary Route(s) of Entry: inhalation, skin contact

Eye Hazards: Eye contact may cause mild mechanical irritation.

Skin Hazards: Prolonged exposure not likely to cause significant skin irritation. May cause more severe

response if skin is abraded (scratched or cut).

Ingestion Hazards: Product is practically non-toxic if swallowed.

Inhalation Hazards: Product may cause a dust hazard if allowed to dry out and disperse. No adverse effects

are aniticipated from inhalation.

EMERGENCY OVERVIEW

Warning: Wet resin creates a slipping hazard. Toxic fumes may be released in fire situations. Exposure to elevated temperatures can cause product to decompose.

Graver Technologies LLC Ecosorb C-981

4. First Aid Measures

Eye: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes.

Skin: Wash affected areas with soap and water. Get medical attention immediately if irritation

develops.

Ingestion: No emergency medical treatment is necessary.

Inhalation: Remove person from source of exposure to fresh air. Get medical attention if irritation

develops.

5. Fire Fighting Measures

Lower Explosive Limit: N/A Upper Explosive Limit: N/A

Fire & Explosion Hazards:

Product is moist and dust-free. Clean up immediately or keep moist until cleanup can be initiated. Product is easily rewetted with a fine water mist. If product dries out and is allowed to become airborne, it may cause a dust explosion hazard when in high concentrations such as within confined spaces. Keep dust away from heat, sparks and flames.

Extinguishing Media:

Use water, dry chemical, or CO2. Use water to cool fire-exposed containers.

Fire Fighting Instructions:

Firefighters should wear self-contained breathing apparati and full protective gear. Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and to prevent re-ignition. Remove product from building if safe to do so. Cool surroundings with water to localize the fire zone.

6. Accidental Release Measures

Avoid generating dust if product dries out - keep moist with water. Pick up released product with appropriate implements & return to original container if reusable, or dispose. Wet material may be slippery.

7. Handling & Storage

Handling Precautions: Follow good handling and housekeeping practices. Avoid spills. Clean up spills while product is still moist to prevent dust and accumulations of dust, or generation of airborne dust. Product can be rewet with a fine water mist to prevent dust. Static electricity can accumulate on dry material.

Storage Precautions: Store in sealed containers in a clean, dry, well-ventillated area away from ignition sources, combustible materials and heat.

Work/Hygienic Practices: After handling, wash thoroughly with soap and water.

Graver Technologies LLC Ecosorb C-981

8. Exposure Controls / Personal Protection

Engineering Controls: Product is moist and dust-free. If product dries out it can be rewetted with a fine water mist

prior to cleanup. If product dries out and rewetting is not possible, be sure there is adequate general and local exhaust ventilation to prevent excessive airborne dust concentrations. Local exhaust ventilation should be provided to maintain exposures below recommended

occupational exposure limits.

Eye/Face Protection: Safety glasses are recommended as minimum industial eye protection when handling bulk

product or performing spill clean-up.

Skin Protection: Protective gloves are recommended to minimize skin contact. Use a lab coat or disposa-

ble coveralls to prevent excessive contamination to personal clothing.

Respiratory Protection: In case of inadequate ventilation, use NIOSH-approved respirator for particulates (e.g.,

N95). Supplied air respirators may be needed for entering confined spaces where product

is stored or handled.

Ingredient(s) - Exposure Limits

resin, strong base anion Single dose oral LD50 has not been determined.

For similar materials: Based on available data, repeated exposures are not anticipated to

cause significant adverse effects.

fiber, cellulose ACGIH TLV-TWA: 10 mg/m3

OSHA PEL-TWA: 15 mg/m3, total dust OSHA PEL-TWA: 5 mg/m3, respirable dust

9. Physical & Chemical Properties

Appearance: Moist, off-white cake Specific Gravity: > 1

Odor: Odorless Packing Density: 28 - 32 lb/ft3

Vapor Pressure: N/A

Chemical Type: Mixture Solubility: Insoluble

Physical State: Solid Evaporation Rate: N/A

10. Stability & Reactivity

Stability: Stable. Exposure to elevated temperatures can cause product to decompose.

Hazardous Polymerization: Will Not Occur

Incompatible Materials: Avoid contact with strong oxidizing agents such as ozone, chlorine, permanganate,

sulfuric acid and nitric acid.

Hazardous Decomposition Products: Thermal decomposition (burning) may produce chlorinated hydrocarbons,

aromatic compounds, hydrocarbons, hydrogen chloride, organic amines.

11. Toxicological Information

Chronic/Carcinogenicity: Neither the product overall nor any of its ingredients are known to be listed as potentially

carcinogenic by NTP, IARC, OSHA, or ACGIH.

Ingredient(s) - Toxicological Data

resin, strong base anion Based on available date, repeated exposures are not anticipated to cause significant

adverse effects.

fiber, cellulose inhal-rat, LC50: >5800 mg/m3 (4-hr)

oral-rat, LD50: >5000 mg/m3

Graver Technologies LLC Ecosorb C-981

12. Ecological Information

Ecotoxicological Information: Surface photodegradation is expected with exposure to sunlight. The resin component is not expected to biodegrade.

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste product is not considered to be a hazardous waste. Dispose of material in approved landfill. Avoid dispersal of spilled material and runoff into soil, waterways, drains and sewers.

14. Transport Information

Not regulated for transportation.

15. Regulatory Information

U.S. Regulatory Information: Toxic Substance Control Act (TSCA): All ingredients of this product are listed on the TSCA 8(b) Chemical Substance Inventory or are exempt.

Product is not classifiable under any of the five SARA Title III hazard ratings.

SARA Section 313 Notification: This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Canadian Regulatory Information: This product is not regulated or controlled under WHMIS (Canada).

European Union (EU) Regulatory Information: European Union Safety Phrases-

S7/9 - Keep container tightly closed and in a well-ventillated place

16. Other Information

NFPA Ratings	Health: 0 Fire: 0	HMIS Ratings Health: 0 Fire: 0
Reactivity: 0		Reactivity: 0 Personal Protection: A

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for her/his particular purpose(s).

Graver Technologies LLC