

**BIGDOG**<sup>®</sup>  
— MOWER CO. —

**REX**  
**SERIES**



**REX**

AVAILABLE DECK SIZES

34" - 42"



**REX**<sup>MP</sup>

AVAILABLE DECK SIZES

34" - 48"

# REX MP

**7** YEAR RESIDENTIAL WARRANTY  
INDUSTRY LEADING LIMITED OR 100 HOUR

**Heavy-Duty Frame**  
1" x 2" steel frame making it one of the toughest and most durable in its class.

**Welded Steel Deck**  
Durable 11 ga. welded fabricated steel deck add durability & extends mower's life. (Compared to other brand's cheap stamped decks).

**Premium Seat**  
Bolstered with built-in lumbar support.

**Premium Power**  
Briggs & Stratton PXi engine.

**Foot Operated Deck Lift**  
Easily adjust the deck height between 1.5" - 4.5" with less effort than hand-operated levers on other brands.

**18" BigBite™ Drive Tires**

**Compact size**  
Easily fits through most gates making backyard mowing easy and ideal for garage storage.

IDEAL FOR UP TO  
**1**  
ACRE



## FEATURES FOUND ON THE REX

# REX

- **16" Rear Tires**

- **Briggs & Stratton Engine**

PowerBuilt™ 10.5 HP

- **Compact Size**

Easily fits through most gates making backyard mowing easy and ideal for garage storage.



## ACCESSORIES

- Mulch Kit
- Side Catcher  
(Rex Only)
- Catcher Dump from  
Seat Adapter  
(Rex Only)
- Grass Bagger  
(non-powered 2.0 bushels)  
(Rex MP Only)
- Steering Lever Extension Kit
- Armrest Kit  
(Rex MP Only)
- Light Kit
- Stripe Kit
- Always-On LED Light Kit  
(Rex MP Only)





	REX		REX MP		
<b>ENGINE</b>					
Manufacturer	Briggs & Stratton		Briggs & Stratton		
HP	34", 42": 10.5HP - Briggs & Stratton PowerBuilt (Per SAE J1995)		34", 42": 18HP - Briggs & Stratton PXi 48": 20HP - Briggs & Stratton PXi (Per SAE J1995)		
Displacement	344cc		656cc		
Cooling	Air cooled				
Engine Warranty	3 year				
<b>DRIVE SYSTEM</b>					
Type	Dual hydrostatic				
Transmission	ZT-1800				
Speed	Up to 5 mph		Up to 6 mph		
Parking Brakes	Integrated with steering levers				
<b>DECKS</b>					
Cutting Width	34", 42"		34", 42", 48"		
Cutting Heights	1.5" - 4.5"				
Deck Lift	Foot operated				
Depth	4.1"				
Blades	2		34", 42": 2 48": 3		
Blade Length	34": 16.75" 42": 20.5"		34": 16.75" 42": 20.50" 48": 16.50		
Blade Tip Speed	34": 17,500 42": 16,700		34": 17,500 42": 16,700 48": 17,200		
Spindles	Aluminum with 3/4" steel shafts and sealed ball bearings with triple protection seals				
Drive	Electric PTO clutch				
Construction	11 ga. fabricated				
Spindle Mounts	Reinforced 14 ga.				
Impact/Trim Areas	1/4" x 3/4" steel bar				
<b>CONSTRUCTION</b>					
Frame	1" x 2" Steel tubing				
Front Axle	Fabricated with sealed all bearings				
Front Caster Wheels	Sealed ball bearings				
Front Caster Forks	Fabricated 1/4" steel				
<b>GENERAL</b>					
Seat	Molded vinyl seat		Premium bolstered seat with built-in lumbar support		
Fuel Capacity	2.8 quarts		2 gallons		
Cupholder	Yes				
Front Tire	11 x 4				
Drive Tire	16 x 6.5 - 8		34": 18 x 6.5 - 8, BigBite 42", 48": 18 x 8.5 - 8, BigBite		
<b>DIMENSIONS</b>					
Weight	34": 390 lbs 42": 400 lbs		34": 455 lbs 42": 467 lbs 48": 490		
Height	38"				
Length	65.5"				
Width w/Chute	34": 37.5" 42": 43.25"		34": 37.5" 42": 43.25" 48": 48.25"		
Tire Width	34": 35.8" 42": 35.8		34": 35 42", 48": 41"		
Trim Side	34": 0" 42": 3"		34": 0.4 42": 0.3 48": 4.1		
<b>PRODUCTIVITY*</b>					
Acres Per Hour	34": 1.65 42": 2.03		34": 1.65 42": 2.04 48": 2.33		

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

\*\* Specifications are subject to change without notice.