


## AUTOSMART 3X

### Product Overview

The AutoSmart 3X features:

- Output 0-5V, 0-10V, 4-20mA
- Non-contact
- Repeatability error 0,1% full scale
- Interchangeability  $\pm 1.5\%$  full scale
- Resolution approx. 0,1°C (0.2°F)
- Small size sensor




\*IRt/c.3X includes ss mounting bracket & locknuts

### Technical Data

Sensor Range	-35 to 250°C (-31 to 482°F)
Sensor Ambient Temperature Range	-18 to 100°C (0 to 212°F)
Transmitter Ambient Temperature Range	0 to 70°C (32 to 158°F)
Storage Temperature Range	-10 to 70°C (14 to 158°F)
Field of View	3:1 (17°) approximately
Minimum Spot Size	6 mm (0.25")
Spectral Response	5,0 to 20µm
Update Time	Approximately 250 msec.
First Reading Upon Power Up	Approximately 2 seconds
Air Purge	Built-in; designed for severe paint or ink environment

Connector cable	3 m (9.8 ft) 22AWG*4C + F + Jacket black PUR cable OD=5,0 mm -40°C~+105°C
Sensor cable	0,9 m (3 ft) Twisted shielded pair of base thermocouple material (J,K,E,T) Telfon sheated, rated to 200°C (392°F) continuous service
Sensor Dimensions	44,7 x 12,7 mm (1.76" x 0.50" Dia.)
Weight	Sensor: 40g (1.4oz.) with cable. Transmitter: Approximately 50g (1.702oz.)
Housing	Sensor: High strength ABS, hermetically sealed, exceeds NEMA, 4,4x; IP65,67. Two locknuts supplied. Transmitter: Heavy Duty SS, NEMA, IP54
Emissivity Setting	0,90
Power	12 or 24VDC (10%). Shuts off when voltage is functionally low
Power Consumption	$\pm 10\text{mA}$ (without output signal device)
Loop Impedance	(4-20mA models) >500Ω

### Ordering Information



### Dimensions

