## CLOSET LIGHT STANDARD DIMMING



ParadigmLED closet light identified for use in the storage area of a closet. Rated for the storage area of closets per NEC 410.2 & 410.16. Available in multiple wattages and channels.

SPECIFICATION								
	+	+	+	+	+	+		
SERIES	WATTAGE	COLOR TEMP	VOLTAGE	CHANNEL TYPE	LENGTH	LENS TYPE		
CL=Closet Light	20=2.0 W/ft. 45=4.5 W/ft. 60=6.0 W/ft. 70=7.0 W/ft. (18WD30 only)	18WD30=1800-3000K Warm- Dim (7W only) 18=1800K 22=2200K 27=2700K 30=3000K 35=3500K 40=4000K 50=5000K 65=6500K	24=24 Volts	1616=AMC-1616-C 1715=AMC-1715-S	XX" = Custom length (max 90")	C=Clear O=Opal		

### **DETAILS**

2 ΩW/ft¥85lum/W=170	OneFlex20
•	OneFlex45
	OneFlex60
<u> </u>	WarmDim70
7.0 **/10.0514111/***-555	
	output +/- 10%
3	2.0W/ftX85lum/W=170 4.5W/ftX85lum/W=338 6.0W/ftX85lum/W=510 7.0W/ftX85lum/W=598

### NOTE:

All closet lights include LED tape, channel, lens, endcaps, wire lead and mounting clips. All closet lights ship fully assembled.


Suitable for installation in the storage areas of clothes closets.

All Closet Light products on this cut sheet utilize a standard 2 wire scheme and can be controlled with phase dimming.

## ADDITIONAL INFORMATION

### **LENSES**

CRI




### **AMC-1616-C DIMENSIONS**

90+(80+ CRI for 1800K & 2200K)




### **AMC-1715-S DIMENSIONS**



- **A:** 0.68" (17.25mm)
- **B:** 0.48" (12.30mm)
- **C:** 0.59" (15.05mm) **D:** 0.66" (16.76mm)
- **E:** 0.78" (19.90mm)

# SPECIFICATIONS 2-7 W/ft., 24VDC, 90+ CRI 50,000 hours min. (L70) DIMENSIONS Channels are 5/8" x 5/8" UL Listed, file E468751 Listed for direct contact with clothing

### AMC-1616-C MOUNTING CLIPS AMC-1715-S MOUNTING CLIPS





www.paradigmled.com 303.399.0386 | sales@paradigmled.com

In an effort to continually improve our products, we reserve the right to change them without prior notice.



Project	
Type	