

BUREAU VERITAS
Certification



'S' Mark Licence

Awarded to

NIAGARA SAWMILLING CO. LTD

74 Kennington Road, Kennington, Invercargill 9871, New Zealand

Bureau Veritas grants the above organization the right to use the Product Certification 'S' Mark as shown below only in respect of the products described and detailed in the Schedule to this Licence and manufactured in accordance with the requirements of the Standard indicated below under an approved Quality Management System. The Licence is granted subject to the 'Bureau Veritas Conditions of Service' and the 'Rules governing the use of Product Certification Licences'.

STANDARD

AS/NZS 1328.1:1998

Glued laminated structural timber

Part 1: Performance requirements and minimum production requirements

Licence No: 2700

Date Granted: 3 April 2009

Revalidated: 2 April 2021

Expiry Date: 2 April 2026

Signed on behalf of Bureau Veritas

Sam Guindi
Product Certification Manager



This Licence and its associated Schedule remain the property of Bureau Veritas and must be returned if certification is terminated. The constant compliance with the certification requirements is confirmed by regular surveillance measures from Bureau Veritas. In the case of serious non-compliance the certification will be withdrawn and deleted from the Register.

To check the validity of this certificate please contact: **Bureau Veritas Australia Pty Ltd**
Issuing office: Bureau Veritas Pty Ltd, 3/435 Williamstown Road, Port Melbourne, Victoria, 3207



SCHEDULE TO PRODUCT CERTIFICATION LICENCE NO: 2700

LICENCE DETAILS

Scheme: 'S' Mark Product Certification
Licensee: NIAGARA SAWMILLING CO. LTD
Address: 74 KENNINGTON ROAD, KENNINGTON, INVERCARGILL 9871, NEW ZEALAND



CONFORMANCE REQUIREMENTS

Standard: AS/NZS 1328.1:1998 Glued laminated structural timber
Part 1: Performance requirements and minimum production requirements
Quality System: Product Certification Quality System Requirements (QSR)

CERTIFIED MODEL OR TYPE

PRODUCT DESCRIPTION

Glued laminated timber members for structural use.

SPECIES

Pinus Radiata

DESIGN STRENGTH

14MPa – GL8

SERVICE CLASS

1, 2 & 3

Service class 3 has been approved through initial type testing. Delamination test facility for ongoing production must be in place before compliance claim can be made for Service Class 3.

Note: If JAS method is used, this must be disclosed to purchasers specifying product compliant to AS/NZS 13281:1998.

ADHESIVES

PUR Purbond HB line

PUR Purbond HB line

Adhesives shall be chosen to suit the end use of the product and be in accordance with clause 2.3

Revision Date: 2 April 2021

