

# LIFT-GARD

***Lift-Gard's robust construction and integral frame protects vertical bucket elevators from explosion damage***



Designed specifically to protect vertical bucket elevators, Elfab's Lift-Gard explosion venting panel features a robust construction with an integral outer frame.

The frame protects the panel from vibrations and harsh operating conditions. The non-fragmenting design allows full opening of the venting panel in the event of an explosion to ensure maximum safety.

Lift-Gard is a reliable, cost-effective solution that is easy to install. In addition, it is the only flat explosion vent to combine an integral frame with an ATEX-approved burst detection system in a single product.

## Sizes

- Internal dimensions (mm): 305x299 – 1140x655
- External dimensions (mm): 385x379 – 1220x735

## Set Pressure Range

- 0.1 barg @ 15/30°C

## Performance Tolerance

- +/- 25%

**Let us help you with all  
your pressure relief questions.**

**UK office | North Shields**

+44 (0)191 293 1234 | [uksales@osecoelfab.com](mailto:uksales@osecoelfab.com)

**US office | Broken Arrow**

+1 (918) 258 5626 | [info@osecoelfab.com](mailto:info@osecoelfab.com)

[osecoelfab.com](http://osecoelfab.com)

**REQUEST A QUOTE FOR  
LIFT-GARD**





Size range	Internal dimensions (mm): 305x299 – 1140x655 External dimensions (mm): 385x379 – 1220x735
Vent area	0.08 m <sup>2</sup> to 0.87 m <sup>2</sup> (0.86 ft <sup>2</sup> to 9.3 ft <sup>2</sup> )
Burst pressure range	0.1 barg to 0.5 barg (0.7 psig to 7 psig)
Standard burst pressure offering	0.1 barg @ 15/30°C
Temperature range	-40°C to 70°C
Operating ratio	50%
Performance tolerance	25%
Vacuum capability	Back-pressure capable
Vent-Tel Detection	Yes (Optional but recommended)
Accessories	Integral frame
Shapes available	Rectangle
Materials available	Stainless steel as standard

## Certifications

ATEX

## Related Products

### Sensors

Vent-Tel

### Accessories

Frames

Gaskets

### Explosion Vents

MV Panel Range

EB Explosion Vents

Hygienic Vent

MV-BE

CRVC

CRP

GLVF

# Lift-Gard

## Dimensions



INTERNAL DIMENSIONS (mm)	EXTERNAL DIMENSIONS (mm)	VENT AREA (m <sup>2</sup> )
178 x 478	258 x 558	0.08
228 x 748	308 x 828	0.16
278 x 466	358 x 546	0.12
308 x 508	388 x 588	0.15
358 x 658	438 x 738	0.22

# Lift-Gard

## Vent Spacing

Dust Kst (bar.m/s)	Maximum spacing between vents (m)*
0-100	12
101-150	9
151-200	6
200+	4

\*Assumes a Pstat of 0.1barg and a Pred of not less than 0.4barg